



OPTIMIZATION OF POWER FROM FOOD WASTE USING MEMBRANE-LESS MICROBIAL FUEL CELL

by

NADIRA ANANDITA

A dissertation submitted in the partial fulfilment of the requirements for the degree of
Bachelor of Technology (B.Tech) in the field of Bioprocess Technology
School of Industrial Technology Universiti Sains Malaysia

July 2020



**PUSAT PENGAJIAN TEKNOLOGI INDUSTRI
UNIVERSITI SAINS MALAYSIA**

**BORANG PENYERTAAN DISERTAI MUTAKHIR
SATU (1) NASKAH**

Nama Penyelia: DR. MUAZ MOHD ZAINI MAKHTAR


Bahagian: TEKNOLOGI BIOPROSES

Saya telah menyemak semua pembetulan/pindaan yang dilaksanakan oleh
Eneik/Puan/Cik NADIRA ANANDITA

mengemui disertainya sebagaimana yang dipersetujui oleh Panel Pemeriksa di Viva
Voceny.

2. Saya ingin mengesahkan bahawa saya berpuashati dengan pembetulan/pindaan
yang dilaksanakan oleh calon.

Sekian, terima kasih.


DR. MUAZ BIN MOHD ZAINI MAKHTAR
Senior Lecturer
Bioprocess Technology Division
School of Industrial Technology,
Universiti Sains Malaysia,
11800 Penang, Malaysia

(Tandatangan dan cop)

18 JUN 2020

Tarikh

DECLARATION BY AUTHOR

This dissertation is composed of my original work and contains no material previously published or written by another person except where due reference has been made in the text. The content of my dissertation is the result of work I have carried out since the commencement of my research project and does not include a substantial part of work that has been submitted to qualify for the award of any other degree or diploma in any university or other tertiary institution.

A handwritten signature in black ink, appearing to read "Nadira Anandita".

Nadira Anandita
June 2020

ACKNOWLEDGMENT

I would like to express my sincere appreciation and gratitude to my final year project Supervisor Dr Muaz Mohd Zaini Makhtar for his advice and guidance throughout this project. His commitment and passion for this project helps me to improve my skills and knowledge. Special thanks to Encik Asmaizan and Puan Najma for their help and guidance to carry out my lab work. Not to forget, my friend Mirza Faisal who is also under supervision Dr. Muaz, as well my Master student senior, Najib Ikmal who willing to lend hand and knowledge assisting throughout this study.

A massive thanks to all my classmates who give moral support and guidance in order to complete my project. Not to forget my fellow FYP mates who are willing to lend hand and support to finish this project. I also would to thanks the School of Industrial Technology for the facilities provided which do help me a lot to finish my project.

Last but not least, big thanks to my beloved parents for their huge sacrifice and support that encourage me to do this research project and throughout my study in Bachelor of Bioprocess Technology. Without them I might not be able to be where I am right now and this project as well as the degree is my little gift from me.

Nadira Anandita

June 2020

TABLE OF CONTENTS

	Page
ACKNOWLEDGEMENT	iv
TABLE OF CONTENTS	v
LIST OF TABLES	viii
LIST OF FIGURES	ix
LIST OF SYMBOLS	x
LIST OF ABBREVIATIONS	xi
ABSTRAK	xii
ABSTRACT	xiii
CHAPTER 1 INTRODUCTION	
1.1 Research background	1
1.2 Problem statement	2
1.3 Research objectives	3
1.4 Scope of work	4
1.5 Thesis organization	4
CHAPTER 2 LITERATURE REVIEW	
2.1 Energy generation	5
2.1.1 Renewable energy	7
2.1.1(a) Solar	7
2.1.1(b) Wind	7
2.1.1(c) Hydro	7
2.1.1(d) Biomass	7
2.1.2 Non-renewable energy	9
2.1.2(a) Coal	10
2.1.2(b) Crude Oil	11
2.1.2(c) Natural gas	11
2.2 Microbial Fuel Cell	12

2.2.1	Microbial Fuel Cell History	12
2.2.2	Microbial Fuel Cell versus Conventional Fuel cell	12
2.2.3	Microbial Fuel Cell concept	12
2.2.3(a)	Biological	12
2.2.3(b)	Chemical	13
2.2.3(c)	Electrical	14
2.2.4	Microbial Fuel Cell design	15
2.2.4(a)	Single chamber	16
2.2.4(b)	Double chamber	16
2.2.4(c)	Stack	17
2.2.4(d)	Flat plate	17
2.2.4(e)	Tubular	18
2.2.5	Microbial Fuel Cell substrates	19
2.3	Food waste	20
2.4	Effect of parameter in MFC	20
2.4.1	moisture	20
2.4.2	Electrode distance	21
2.4.3	Temperature	21
2.4.4	pH	21
2.5	Polarization curve method in MFC	22

CHAPTER 3 METHODOLOGY

3.1	Equipments and Chemicals	23
3.2	Research methodology flow chart	24
3.3	Sample Collection	25
3.4	MFC configuration	25
3.5	Preparation of inoculum	26
3.6	Experimental Design	26

3.6.1 Optimization of electricity generation using one-factor-at-one-time (OFAT)	26
3.6.1(a) Effect of pH	26
3.7 Analytical method	27
3.7.1 Determination of micronutrients and trace elements	27
3.7.2 Determination of macronutrients	27
3.7.3 Determination of substrate degradation efficiency (SDE)	28
3.7.4 Determination of electricity generation	29
3.7.5 Determination of biomass	29
3.7.6 Specific growth rate electrogenic bacteria	30
3.7.7 Doubling time to each electrogenic bacteria	30
CHAPTER 4 RESULTS AND DISCUSSIONS	
4.1 Proximate analysis of food waste	32
4.2 Preliminary study on growth kinetic of different strain of EB in batch culture.	34
4.3 Effect of pH in ML-MFC	36
4.3.1 Effect of pH on EB Voltage generation and substrate degradation efficiency (SDE) in the ML-MFC	36
4.3.2 Effect of pH on EB growth in the ML-MFC	39
4.3.3 Effect of pH on Voltage generation and biomass growth in the ML-MFC.	41
4.4 ML-MFC performance	42
CHAPTER 5 CONCLUSION AND RECOMMENDATION	
5.1 Conclusion	45
5.2 Recommendations	45
REFERENCES	46
APPENDIX	50

LIST OF TABLES

	Caption	Page
Table 2.1	List of microbial fuel cell substrates	19
Table 3.1	List of chemicals used and information	23
Table 3.2	List of equipment used and information	23
Table 4.1	Compounds analyse in food waste.	32
Table 4.2	EB growth rate and doubling time	35
Table 4.3	The comparison of the specific growth rate and doubling time for each EB.	35
Table 4.4	Result of voltage generation and COD removal using one-factor-at-a-time (OFAT).	38
Table 4.5	Power density at each pH	42

LIST OF FIGURES

Caption	Page
Figure 2.1 World energy generation in 2018 by IEA	6
Figure 2.2 Pie chart electricity generation in Malaysia by Energy commission Malaysia 2017	10
Figure 2.3 Respiratory chain of anode and cathode reaction(Horan et al., 2018)	14
Figure 2.4 MFC pathway	15
Figure 2.5 Single chamber MFC	16
Figure 2.6 Double chamber MFC	16
Figure 2.7 Stacked MFC	17
Figure 2.8 Flat plated MFC	17
Figure 2.9 Tubular MFC	18
Figure 2.10 Flowchart of food waste treatment by E-idaman sdn bhd.	21
Figure 3.1 Flowchart of methodology	24
Figure 3.2 ML-MFC design	25
Figure 4.1 The trend of biomass vs Time of EB <i>geobacter</i> , <i>bacillus</i> , and mixed of <i>geobacter</i> and <i>bacillus</i> .	34
Figure 4.2 Voltage generation of all varied pH	37
Figure 4.3 Chemical oxygen demand versus time of varied pH	38
Figure 4.4 Biomass ML-MFC of varied pH	40
Figure 4.5 Biomass and Voltage profile of pH 8	41
Figure 4.6 Graph of power density over varied resistance of varied pH	43
Figure 4.7 Polarization curve pH 8	44

LIST OF SYMBOLS

Caption

$^{\circ}\text{C}$	Celsius
kg/m^3	kilogram per metre cube
mg	milligram
NaOH	Sodium hydroxide
NaClO ₂	Sodium chlorite
c/kW.h	Cent per kilo Watt hour
mg / L	Milligram per litre
mW / m ²	milliwatt per meter cube
g	gram
M	Molar
HNO ₃	Nitric acid
NAD ₊	nicotinamide adenine dinucleotide
FADH ₂	Flavin adenine dinucleotide
CO ₂	Carbon dioxide
H ₂ O ₂	Hydrogen peroxide
V	Volt
I	Current
R	Resistance
P	Power

LIST OF ABBREVIATIONS

Abbreviation	Definition
MFC	Microbial fuel cell
ML-MFC	Membrane less - microbial fuel cell
COD	Chemical oxygen demand
SDE	Substrate degradation efficiency
OFAT	One-factor-at-a-time
RE	Renewable energy
NRE	Non renewable energy
cm	Centimetre
MW	Microgram
mm	Millimetre
Abs	Absorbance
EJ	Exojoule
mV	milivolte
ATP	adenosine triphosphate
ppm	Parts per million
hr	Hour
mL	millilitres

Abstrak

Bahan bakar fosil telah menyokong perindustrian dan pertumbuhan ekonomi negara-negara selama berabad-abad yang lalu dan jelas bahawa tidak dapat bertahan dalam jangka waktu yang lebih lama. Dalam kajian ini, Microbial Fuel cell (MFC) berpotensi untuk menghasilkan tenaga elektrik dan pada masa yang sama dapat mengurangkan banyak sisa makanan (1,64 kg / hari, sekitar 8 tan / tahun) yang dibuang di tempat sampah. MFC yang dikendalikan secara elektrokimia menggabungkan bakteria elektrogenik (EB) yang bertindak sebagai biopemangkin untuk menghasilkan elektrik. Prestasi MFC menggunakan sisa makanan dinilai menggunakan kaedah satu-faktor-pada-satu-saat (OFAT). Kajian ini fokus pada pengoptimuman pH untuk menghasilkan penjanaan tenaga yang lebih baik. Untuk menentukan elektrik yang dihasilkan, keluk polarisasi digunakan untuk menilai prestasi MFC. Permintaan oksigen kimia (COD) sisa makanan juga dipelajari. Pengoptimuman keadaan pH di MFC di bawah pH antara 5 hingga 9. Hasil kajian menunjukkan bahawa pH 8 adalah pH yang paling sesuai untuk strain *Bacillus* yang dipilih untuk eksperimen ini. Dengan voltan yang dihasilkan 807 mV, biojisim tertinggi 35.46 mg / L, dan ketumpatan kuasa menghasilkan 373.3 mW / m². Kesimpulannya, keadaan persekitaran pH di MFC akan mempengaruhi kecekapan pengeluaran tenaga. Peningkatan dalam EB juga meningkatkan voltan dalam ML-MFC, membuktikan bahawa jumlah EB dan voltan EB dikaitkan dengan pertumbuhan EB.

Abstract

Fossil fuels have supported the industrialization and economic growth of countries during the past centuries and it is clear that they cannot indefinitely sustain in a longer time. In this study, Microbial Fuel cell (MFC) had potential solution to generate electricity power and at the same time could reduce the abundant of food waste (1.64 kg/daily, around 8 tonnes/year) which dumped in the landfill. The MFC operated electrochemically incorporate electrogenic bacteria (EB) acted as a biocatalyst in order to produce electricity. The performance of the MFC using food waste is evaluated using one-factor-at-a-time (OFAT) method. the optimization performance of the MFC using food waste was evaluated using method of one factor at one time (OFAT) and it was focused to pH for power generation. To determine the generated electricity the polarization curve was used to evaluate the performance of MFC. The chemical oxygen demand (COD) of food waste is studied. Optimization of pH condition in MFC under certain pH ranging from 5 to 9, with other condition. Results shows that pH 8 is the most suitable pH for *Bacillus* strain that was chosen for this experiment. With voltage generated resulted 807 mV, highest biomass produced 35.46 mg/L, and power density produced 373.3 mW/m². In conclusion, pH environment condition in MFC will affect the efficiency of performance for energy production. The increase in EB biomass also increased the voltage in the ML-MFC, proving that EB biomass and voltage were associated with growth.