

**HOUSEHOLD ELECTRICAL POWER METER USING EMBEDDED RFID
WITH WIRELESS SENSOR NETWORK PLATFORM**

by

WASANA BOONSONG

**Thesis submitted in fulfillment of the requirements for
the degree of Doctor of Philosophy**

July 2016

**HOUSEHOLD ELECTRICAL POWER METER
USING EMBEDDED RFID WITH WIRELESS
SENSOR NETWORK PLATFORM**

WASANA BOONSONG

**UNIVERSITI SAINS MALAYSIA
2016**

ACKNOWLEDGEMENTS

Over and above everything, I offer my humble gratitude of the most goodness to Allah S.W.T for blessing me with opportunities and grace to meet with the humanitarian Aj. Bhatra Panas-ampol, Aj. Weerayut Jantharaksa and Encik Amad Nazdri Bin Jusoh, who encourage and promote me to receive the scholarship. Foremost, I would like to express my sincere gratitude to my supervisor Professor Dr. Widad Ismail for her continuous supporting of my study and research, for her patience, motivation, enthusiasm and immense knowledge.

Apart from this, my gratitude also goes out to the staffs of the school of Electrical and Electronic Engineering, USM, especially the technical staff. I would also like to thank all my friends in our Auto-ID laboratory Research Group for their cooperation and company.

I would like to thank the Rajamangala University of Technology Srivijaya, which is sponsoring the scholarship throughout the study period. The USM RU (Research University) grant secretariat and Postgraduate Research Grant Scheme (PRGS) for sponsoring the development of the in house built in RFID devices.

Lastly is my deepest appreciation to my beloved parents, Paw Chaleaw and Mea Noowin Boonsong who have never stopped praying and waiting for my success. Similarly, thank to my kids, Nong Choompoopantip and Nong Maninthorn who are my big importance power to be success and through all problems in my life and included of the encouraged and supported persons during my Phd. study.

TABLE OF CONTENTS

	page
ACKNOWLEDGEMENT	ii
TABLE OF CONTENTS	iii
LIST OF TABLES	ix
LIST OF FIGURES	xi
LIST OF ABBREVIATIONS	xx
ABSTRAK	xxv
ABSTRACT	xxvii
CHAPTER ONE – INTRODUCTION	1
1.1 Introduction	1
1.2 Problem Statement	3
1.3 Research Objectives	4
1.4 Scope and Project Limitations	5
1.5 Thesis Outline	6
CHAPTER TWO – LITERATURE REVIEW	7
2.1 Introduction	7
2.2 Review of Electrical Power Meters	9
2.2.1 Conventional Electrical Power Meter	9
2.2.2 Automatic Meter Reading	12
2.2.3 Smart Meter	14
2.3 Review of RFID System Applications	20
2.3.1 RFID Tags	21
2.3.2 RFID Readers	28
2.4 Review of WSN Platform Applications	30
2.5 Applications of RFID with WSN	36

2.6	Wireless Technologies	37
2.7	Machine-to-Machine (M2M) Communications	42
2.8	Related Works of Automated Energy Monitoring Embedded an Active RFID with WSN Platform	44
2.9	Summary	54
 CHAPTER THREE – METHODOLOGY		 55
3.1	Introduction	55
3.2	Overview of the Proposed Wireless Energy Monitoring System Requirements	56
3.2.1	The Embedment for the Proposed Data Monitoring System	59
3.2.2	Power Management Design for WSN Efficiency and Lifetime Issue	60
3.2.3	Real Time Data Monitoring	62
3.2.4	Advantages of M2M Wireless Communication	63
3.3	Developed Hardware Application Requirements	66
3.3.1	Embedded Active RFID System with WMSN Application	68
3.3.2	Development of the EPRFID with Universal Household Power Meter	71
3.3.3	Microcontroller	72
	3.3.3.1 Communication Mechanism for Controller	75
3.3.4	Current Sensor	77
3.3.5	Voltage Sensor	81
	3.3.5.1 Concept of Voltage Sensor Design	83
	3.3.5.2 Communication Mechanism for Voltage Sensor	85
3.3.6	Energy Requirements	86
3.3.7	Real-Time Clock (RTC) and Memory Allocation	89

3.3.8	Display Unit	92
3.3.9	Components Embedment of the EPRFID System	94
3.4	Realization of the Proposed EPRFID System's Roles	97
3.5	The Standalone RFID Tag for Performance Comparison	99
3.6	The Proposed EPRFID Reader	100
3.7	Enabling of the Proposed EPRFID System	103
3.7.1	Data Communication	107
3.7.2	Mode of Operation	109
3.8	Configuration of the Proposed EPRFID System with WSN Platform	113
3.9	Summary	116
 CHAPTER FOUR – SOFTWARE DEVELOPMENT AND OVERALL IMPLEMENTATION		 118
4.1	Introduction	118
4.2	The Proposed EPRFID System	119
4.2.1	The Proposed Architecture Design of the Active EPRFID Tag	119
4.2.2	Communication Method Design for EPRFID System	121
4.2.3	Voltage Sensor Programming	124
4.2.4	Current Sensor Programming	125
4.2.5	Microcontroller	120
4.2.6	Real Time Clock (RTC) and Memory	122
4.3	Embedment Methods for Wireless Active RFID Sensors Connecting to WSN Communication	137
4.3.1	EPRFID Reader	139
4.3.2	Router/End Device	143

4.4	The Communication Scheme Design of the Proposed EPRFID System	148
4.5	Design and Development to Improve the WMSN Communication for the Proposed EPRFID System	152
4.5.1	Collision Avoidance	153
4.5.2	Overhearing Avoidance	153
4.5.3	Energy Saving versus Increased Latency Analysis	155
4.6	The Graphical User Interface (GUI) on Host Computer Design	157
4.6.1	Time Parameters Programming Design	164
4.6.1.1	Time Sent	164
4.6.1.2	Time Received	165
4.6.1.3	Time Delay	166
4.6.2	Electricity Information Parameters	166
4.7	Experimental Testing and Measurements Planning	167
4.7.1	The Proposed EPRFID System Load Testing	168
4.7.2	The Calibration of the Proposed EPRFID System	168
4.7.3	The Proposed EPRFID System Calibration for Power Transmit	170
4.7.4	Energy Analysis	170
4.7.5	The Anti Collision Test	171
4.7.6	Radiation Pattern	172
4.7.7	Maximum Read Range	173
4.7.8	Data Collection and Latency Delay Time	174
4.7.9	Throughput Evaluation	175
4.8	Summary	176

CHAPTER FIVE – EXPERIMENTAL RESULTS AND DISCUSSION	177
5.1 Introduction	177
5.2 The Proposed EPRFID System Load Testing	178
5.2.1 The Standalone Electrical Power Meter Load Testing	178
5.2.2 The Electrical Power Meter with the Proposed EPRFID Tag	179
5.2.3 Performance Analysis for Load Testing	180
5.2.4 The Development of the Proposed EPRFID System	184
5.3 The Calibration of the Proposed EPRFID System	187
5.3.1 The Voltage Calibration	188
5.3.1.1 Microcontroller	188
5.3.1.2 RF Transceiver	189
5.3.1.3 Current Sensor, RTC and Memory and Display Modules	191
5.3.2 The Current Calibration	191
5.3.2.1 Microcontroller	191
5.3.2.2 Wireless RF Transceiver Part	193
5.3.2.3 The Current Sensor Module	195
5.3.2.4 The Integrated RTC with Memory Module	196
5.3.2.5 Display Module	198
5.3.3 Analysis and Discussion of the Current Calibration Test	199
5.3.3.1 Standalone RFID	199
5.3.3.2 Proposed EPRFID System	200
5.4 The Proposed EPRFID System Calibration for Power Transmission	202
5.5 Energy Analysis	208
5.5.1 The Measured Current Consumption Analysis	209
5.5.2 Calculated Current Consumption Analysis for 60 s	214

5.5.3	The Measured Current Consumption for 60 s	216
5.6	The Energy Tradeoffs based on Measured DC Characteristics	217
5.7	The Anti Collision Performance Test	225
5.7.1	Tag Collection Process of the CSMA/CA Algorithm versus Distance Range for Single Hop Communication	227
5.7.2	Tag Collection Process of the CSMA/CA Algorithm versus Distance Range for the Multiple Hops Communication	230
5.7.3	Tag Collection Process of the CSMA/CA Algorithm versus Time Interval between Messages for Single Hop Communication	232
5.7.4	The Tag Collection Process of the CSMA/CA Algorithm versus Time Interval between Messages for the Multiple Hops Communication	236
5.8	The Maximum Read Range Measurement	238
5.8.1	The Indoor Environment Test	238
5.9.2	The Outdoor Environment Test	241
5.9	Tag Collection and Latency Delay Time	246
5.9.1	Tag Collection Time and Latency of the Multiple Hops	248
5.10	Throughput Evaluations	250
5.12	Summary	253
CHAPTER SIX – CONCLUSION AND FUTURE WORK		264
6.1	Conclusion	259
6.2	Future Work	261
REFERENCES		264
LIST OF PUBLICATIONS		285
APPENDIXES		

LIST OF TABLES

		page
Table 2.1	Comparison between the active and passive RFID technologies	24
Table 2.2	The comparison between ZigBee and other wireless devices	39
Table 2.3	The previous works related with wireless energy monitoring embedded RFID and WSN platform	53
Table 3.1	The sleep mode configurations	111
Table 3.2	Sample sleep mode currents	111
Table 3.3	The proposed EPRFID specifications	117
Table 5.1	Comparison of the three household electrical power meters without and with the EPRFID modules	180
Table 5.2	Comparison of the developed household electrical power meters without and with the EPRFID modules	186
Table 5.3	The measured current consumption and interval time for the standalone RFID and EPRFID tags according to mode of operations	213
Table 5.4	The calculated current consumption for the proposed standalone RFID tag	214
Table 5.5	The calculated current consumption for the proposed EPRFID tag	214
Table 5.6	Time usage in percentage of the proposed EPRFID and standalone RFID systems for each mode in 60 s	215
Table 5.7	The calculated current consumption of the proposed EPRFID and standalone RFID systems for each mode in 60 s	216
Table 5.8	The measured current consumption of the proposed EPRFID and standalone RFID systems for each mode in 60 s	217
Table 5.9	The power consumption of the proposed EPRFID and standalone RFID systems for the time period of 60 s based on the measured DC characteristics	219

Table 5.10	The multi-hop transmitting power for a period of 60 s	221
Table 5.11	The multi-hop receiving power for a period of 60 s	222
Table 5.12	The multi-hop idle power for a period of 60 s	223
Table 5.13	The multi-hop sleep power for a period of 60 s	224
Table 5.14	The total power of a multi-hop of 60 s	224
Table 5.15	The proposed EPRFID specifications compared with standalone RFID	253
Table 5.16	Comparison with other patented systems	255

LIST OF FIGURES

	page
Figure 2.1 Basic block diagram of an electronic energy meter (EEM)	10
Figure 2.2 Principle diagram of digital energy metering system	12
Figure 2.3 Modern electrical energy measuring chain	13
Figure 2.4 Information flow using a smart meter	15
Figure 2.5 Parts involved in a smart metering system diagram	16
Figure 2.6 Feature comparison between different kinds of meters	19
Figure 2.7 Passive RFID System	23
Figure 2.8 Block diagram of an active RFID tag	24
Figure 2.9 The smart meter hardware structure	27
Figure 2.10 Block diagram of the proposed an embedded active RFID Tag with switch system	28
Figure 2.11 Simple architecture of RFID reader	29
Figure 2.12 Improved RFID reader architecture	29
Figure 2.13 Architecture of wireless sensor networks	31
Figure 2.14 Basic network topologies	33
Figure 2.15 ZigBee in comparison with the wireless standards on range	38
Figure 2.16 The ZigBee standard and IEEE 802.15.4	40
Figure 2.17 Implementing ZigBee in active RFID devices	41
Figure 2.18 Main architecture of M2M technology	43
Figure 2.19 Block diagram of typical embedded system	45
Figure 2.20 Block diagram of the switch system	47
Figure 2.21 Block diagram of a smart meter	47
Figure 2.22 The overall proposed smart metering	48
Figure 2.23 The scenario of television white space (TVWS)	49

Figure 2.24	Block diagram of proposed electricity theft control system using GSM network	50
Figure 2.25	Schematic diagram of the smart energy meter	51
Figure 2.26	Proposed overall system of smart meter	51
Figure 3.1	The proposed wireless monitoring system concept for household electrical power meter	56
Figure 3.2	Overview proposed system architecture components	57
Figure 3.3	The proposed overall framework of system architecture	58
Figure 3.4	(a) Typical power supply management for active RFID tag and (b) contribution of energy solution for active RFID tag	61
Figure 3.5	The proposed block diagram of MCU main board worked in sleeping mode function for WSN platform	62
Figure 3.6	Comparison of conventional meter reading to the proposed wireless data monitoring using embedded RFID with WSN platform	65
Figure 3.7	Main research procedures for hardware development	68
Figure 3.8	Block diagram of (a) existing RFID tag and (b) developed block diagram of embedded active RFID tag according to the proposed system requirements	70
Figure 3.9	Architecture application development of a residential power meter developed with the proposed system	72
Figure 3.10	Data connection between microcontroller and ZigBee-Pro	73
Figure 3.11	The developed connection design of microcontroller	74
Figure 3.12	The developed UART source code for data communication between MCU and RF transceiver module	76
Figure 3.13	Connection data flow diagram in a UART interface environment between RFID tag and ATmega328 for the proposed communication system	76
Figure 3.14	Current sensor schematic diagram of the proposed EPRFID system	78

Figure 3.15	Accuracy testing method design of the current sensor module	79
Figure 3.16	Current sensing methodology flowchart of the proposed EPRFID system	80
Figure 3.17	Relations of output voltage versus sensed current	80
Figure 3.18	The block diagram and schematic circuit design of voltage sensor in the proposed EPRFID system	82
Figure 3.19	PCB layout of the proposed voltage sensor	83
Figure 3.20	Voltage calibration flowchart of the proposed EPRFID system	84
Figure 3.21	Connection data flow diagram in ADC interface environment between voltage sensor and ATmega328 microcontroller	85
Figure 3.22	(a) schematic circuit and (b) the PCB layout of RTC and memory module of the proposed EPRFID system	91
Figure 3.23	Developed connection design of RTC & memory unit to communicate with ATmega328	82
Figure 3.24	The flowchart of RTC functional testing	92
Figure 3.25	Display module of the EPRFID device	93
Figure 3.26	The embedded system of the proposed EPRFID prototype	95
Figure 3.27	Functional features of the proposed EPRFID system	99
Figure 3.28	Basic components of the proposed standalone RFID tag system	100
Figure 3.29	Block diagram of the standalone RFID tag	100
Figure 3.30	Block diagram of the proposed EPRFID reader integrated with GUI	101
Figure 3.31	The proposed EPRFID reader schematic	102
Figure 3.32	ZigBee-enabled network of the proposed EPRFID reader	103
Figure 3.33	System data flow diagram in a UART-interfaced environment	107
Figure 3.34	UART data packet 0x1F (decimal number “31”) as transmitted through the module	108

Figure 3.35	The internal data flow diagram	108
Figure 3.36	The ZigBee-Pro RF module modes operation	109
Figure 3.37	Syntax for sending AT commands	112
Figure 3.38	M2M process stage for the proposed system	113
Figure 3.39	Flowchart of the M2M communication process	114
Figure 3.40	Data flow from the EPRFID device to EPRFID reader process	115
Figure 4.1	Overall proposed EPRFID system	119
Figure 4.2	Block diagram of the proposed EPRFID tag architecture	120
Figure 4.3	UART data transmission format of the proposed EPRFID system	121
Figure 4.4	The programming code of (a) data sending and (b) data receiving through UART protocol testing of the proposed EPRFID and standalone RFID tag	122
Figure 4.5	The proposed data communication method between MCU and active RFID tag	123
Figure 4.6	The analogue voltage output of voltage sensor for the proposed EPRFID system	124
Figure 4.7	The flowchart of voltage sensor functional design for the proposed EPRFID system	125
Figure 4.8	Pin connection between ACS712 current sensor with ATmega328 microcontroller of the proposed EPRFID system	127
Figure 4.9	The flowchart of current sensor functional design for the proposed EPRFID system	129
Figure 4.10	The flowchart of power consumption calculation subroutine of the proposed EPRFID system	130
Figure 4.11	The flowchart of power consumption recording subroutine of the proposed EPRFID system	131

Figure 4.12	The flowchart of real time generating for the proposed EPRFID system	133
Figure 4.13	Typical system bus configuration	135
Figure 4.14	The flowchart of 24C32 EEPROM for writing data	136
Figure 4.15	The flowchart of 24C32 EEPROM for reading data	137
Figure 4.16	The network formation process of the proposed EPRFID system	138
Figure 4.17	Implementation method of reader-tag communication in duty cycle mode	149
Figure 4.18	Periodic of listening and sleeping mode for the proposed EPRFID protocol	151
Figure 4.19	Timing relationship between an EPRFID tag and EPRFID reader	151
Figure 4.20	The overhearing avoidance mechanism design block of the proposed EPRFID system	154
Figure 4.21	Flowchart of the proposed frame packet collection process for multiple EPRFID tags	157
Figure 4.22	The flowchart of the proposed GUI on host computer	159
Figure 4.23	Monitoring software platform components	160
Figure 4.24	Block diagram system components	161
Figure 4.25	The design of communication module between EPRFID reader and host computer (b) main programming part (b) GUI part	162
Figure 4.26	The proposed design of monitoring software module at the work station	162
Figure 4.27	The monitoring software module design at the work station for the proposed EPRFID system (a) main programming part (b) GUI part	163
Figure 4.28	The programming code of time parameters	164

Figure 4.29	The created GUI in terms of time sent parameter at the host computer	165
Figure 4.30	The design of time received parameter from the EPRFID end device on GUI part	165
Figure 4.31	The design of time delay parameter between sent and received message on monitoring software	166
Figure 4.32	Electricity information monitoring part on work station	167
Figure 4.33	The throughput evaluated by the proposed GUI design	167
Figure 4.34	The flowchart of the transmit power calibration test	169
Figure 4.35	The flowchart of the anti collection test	171
Figure 4.36	Algorithm flowchart of the EPRFID system with the anti-collision protocol	172
Figure 5.1	The tronics power meter T-10 household electrical power meter with appliance load	179
Figure 5.2	The tronics power T-10 digital electrical power meter embedded with the proposed EPRFID module	179
Figure 5.3	Magnitude of power difference for the standalone electrical power meters A, B and C in comparison with the EPRFID modules	181
Figure 5.4	Power differences in terms of the percentage (%) for three electrical power meters A, B and C without and with the EPRFID modules	182
Figure 5.5	Total power consumption of the proposed EPRFID module based on individual blocks (model 1)	183
Figure 5.6	Block diagram of the improved EPRFID system (model 2)	184
Figure 5.7	Comparison the microcontroller board's dropout voltage for both systems compared with the theoretical standard value	189
Figure 5.8	Dropout voltage of the RF transceiver module during the transmission and receiving conditions of both systems compared with the theoretical standard value	190

Figure 5.9	Current consumption of the ATmega328 microcontroller main board during the data transmission and receiving conditions of both systems compared with the theoretical standard value	193
Figure 5.10	Current consumption of the RF transceiver module during the transmission and receiving conditions of both systems	194
Figure 5.11	The current consumption of the current sensor in the EPRFID system during the transmission and receiving conditions	196
Figure 5.12	The current consumption of the RTC integrated with memory module during the data transmission and receiving conditions of the EPRFID module compared with the theoretical standard value	197
Figure 5.13	Current consumption of the display module in the EPRFID system during data transmission and receiving conditions compared with the theoretical standard value	198
Figure 5.14	Current calibration test of the proposed standalone RFID	199
Figure 5.15	Current calibration test in each module of the proposed EPRFID system	201
Figure 5.16	The X-CTU software used for configuration parameters of power transmission of ZigBee-Pro module	203
Figure 5.17	The transmitted power calibration of the EPRFID system using a splitter ended by a terminator	204
Figure 5.18	The measured transmit power versus distance for each transmitted power level test	205
Figure 5.19	The transmitted power calibration test of the EPRFID system using a splitter and a whip antenna	205
Figure 5.20	Comparison of the transmitted power at each level of both systems	206
Figure 5.21	Configuration of the transmitted power calibration test using a T-splitter and a whip antenna	206
Figure 5.22	Power consumption measurement of the proposed EPRFID system	209

Figure 5.23	Current consumption during the transmission cycle for (a) the standalone RFID tag and (b) the proposed EPRFID tag system	210
Figure 5.24	Current consumption during the receiving cycle for (a) the standalone RFID tag and (b) the proposed EPRFID tag system	212
Figure 5.25	Current consumption during the idle cycle for (a) the standalone RFID tag and (b) the proposed EPRFID tag system	212
Figure 5.26	The power consumption based on the measured DC characteristics	218
Figure 5.27	Time interval between messages for 60 s captured by the monitoring station	218
Figure 5.28	Measurement layout of WSN (EPRFID tags-to-reader) based on the multiple hops in a real environment	220
Figure 5.29	The anti-collision test setup	226
Figure 5.30	The monitored data at work station using the developed GUI	228
Figure 5.31	Performance of the CSMA/CA test for a single hop with three end tags	229
Figure 5.32	The performance of the CSMA/CA test via four hops communication with three end tags	231
Figure 5.33	The sending time interval between messages verified by monitoring station	233
Figure 5.34	Successfully received message versus time interval between messages for single hop with three end tags	234
Figure 5.35	Successfully received message versus time interval for multiple tags	235
Figure 5.36	The successfully received messages for the multiple hops (%) versus time interval between messages (s)	236
Figure 5.37	Fixed output amount testing based WiFi standard	237

Figure 5.38	(a) The RSSI values versus distances for the indoor environment in each level of transmission power (b) Zoomed in the RSSIs versus distance ranges at indoor environment at the transmitted power setup level of 10 dBm	240
Figure 5.39	(a) The RSSIs versus distance ranges for an outdoor environment with the transmission power from 2 to 10 dBm (b) Zoomed in the RSSIs versus distances for the outdoor environment at the transmitted power setup level of 10 dBm	243
Figure 5.40	The RSSI values versus distance ranges at the outdoor environment from 100 m to 600 m (measured RSSI) and from 700 m to 1500 m (extrapolated RSSI) at transmitted power value of 10 dBm	245
Figure 5.41	(a) The time delay of the received information and (b) the actual status of a power consumption by GUI	247
Figure 5.42	Tag collection time for the multiple hops communication	249
Figure 5.43	Multiple hops with three tags latency	250
Figure 5.44	Throughput evaluation for the multi-hop communication test	251
Figure 5.45	Normalized throughput in ideal channel and saturated traffic	252

LIST OF ABBREVIATIONS

AC	Alternating Current
ACEL	Alternating Current Electronic Load
ACK	Acknowledge
ADC	Analog-to-Digital Converter
ALU	Arithmetic Logic Unit
AMI	Automated Meter Infrastructure
AMI	Advanced Metering Infrastructure
AMM	Automated Meter Management
AMR	Automated Meter Reading
AMI	Advance Metering Infrastructure
AREF	Analog Reference
ASIC	Application Specified Integrated Circuit
AVR	Automatic Voltage Regulator
BAN	Building Area Network
BDC	Binary Code Decimal
BD	Baud Rate
BP	Back-Propagation
CEP	Complex Event Processing
CH	Channel
CISC	Complex Instruction Set Computer
CMOS	Complementary Metal-Oxide Semiconductor
CPN	Customer Premises Network
CPS	Cyber Physical System

CPU	Central Processing Unit
CR	Cognitive Radio
CSMA/CA	Carrier Sense Multiple Access/Collision Voidance
CT	Current Transformer
CTS	Clear-to-Sent
DCU	Data Concentrator Unit
DMT	Digital Micro Technology
DSO	Distribution System Operator
DTV	Digital Television
EEM	Electronic Energy Meter
EEPROM	Electrically Erasable Programmable Read-Only Memory
EMS	Energy Management System
EPRFID	Embedded RFID module with household electrical Power Meter
EIRP	Effective Isotropic Radiated Power
EV	Electrical Vehicle
FCC	Federal Communication Commission
FFD	Full-Function Device
GIS	Geographic Information System
GSM	Global System for Mobile
GUI	Graphical User Interface
GT	Guard Time
HAN	Home Area Network
H2M	Human-to-Machine
HTAMI	High Traffic-Advanced Metering Infrastructure
IC	Integrated Circuit

ICT	Information and Communication Technology
ID	Identification
IEEE	Institute of Electrical and Electronics Engineers
IoT	Internet of Thing
ISM	Industrial, Scientific and Medical
IT	Information Technology
JEDEC	Joint Electron Device Engineering
KWh	Kilowatts per hour
LAN	Local Area Network
LOS	Light-of-Sight
LTE	Long Term Evolution
MAC	Medium Access Control
MDMS	Meter Data Management System
MCU	Multipoint Control Unit
M2M	Machine-to-Machine
MLF	Micro Lead Frame
NAV	Network Allocation Vector
NGB	Next Generation Broadcasting
NILM	Non-Intrusive Load Monitoring
NIWEM	Non-Intrusive Wireless Energy Meter
NLOS	Non Light-of-Sight
NWK	Network Layer
PAN	Personal Area Network
PC	Personal Computer
PCB	Print Circuit Board

PHY	Physical
PPE	Personal Protective Equipment
PU	Primary User
QFN	Quad-Flat No-Lead
QoS	Quality of Service
RAP	Resource Allocation Problem
RF	Radio Frequency
RFD	Reduced-Function Device
RFID	Radio Frequency Identification
RS	Register Select
RSSI	Received Signal Strength Indication
RTC	Real-Time Clock
RTF	Reader Talk First
RTS	Request-to-Sent
R/W	Read/Write
SCADA	Supervisory Control and Data Acquisition
SCL	Serial Clock Input
SDA	Serial Data Input/Output
SoC	System on Chip
SHR	Self-Healing Ring Network
SM	Smart Meter
SMS	Smart Metering System
SPI	Serial Peripheral Interface
SRAM	Static Random Access Memory
SRAM	Static Random Access Memory