

**COMPATIBILITY AND DEGRADABILITY OF
KENAF-FILLED LINEAR LOW DENSITY
POLYETHYLENE/POLYVINYL ALCOHOL
COMPOSITES**

PANG AI LING

UNIVERSITI SAINS MALAYSIA

2018

**COMPATIBILITY AND DEGRADABILITY OF
KENAF-FILLED LINEAR LOW DENSITY
POLYETHYLENE/POLYVINYL ALCOHOL COMPOSITES**

by

PANG AI LING

**Thesis submitted in fulfillment of the
requirements for the degree of
Doctor of Philosophy**

August 2018

ACKNOWLEDGEMENT

First and foremost, I would like to express my greatest appreciation to my supervisor, Prof. Dr. Hj. Hanafi Ismail for his valuable guidance, support and consistent encouragement during my study in USM. It is a great opportunity to complete my doctoral programme under his supervision. I would also like to express my gratitude to my co-supervisor, Prof. Madya. Dr. Azhar Abu Bakar, who always support and spending his precious time to teach and help me during my research study.

Most of the results presented in this thesis would not have been accomplished without a close collaboration with few laboratories. Hence, I would like to take this opportunity to thank the technical staffs from laboratories namely, Mr. Shahril, Mr. Suharudin, Mr. Mohamad Hassan, Mr. Rashid, Mr. Khairi, Mr. Faisal, Mr. Shahrizol, and Mr. Azrul. My humble regards to other whose names are not mentioned here for their kind assistance. Furthermore, I wish to thank Dean of the School of Materials and Mineral Resources Engineering (SMMRE), and all administrative as well as technical staffs of SMMRE, who has been kind enough to advise and help me in completing my study.

I am also thankful to my friends especially Dr. Mohsen Ahmadipour, Dr. Norshahida, Dr. Mathialagan, Dr. Sam Sung Ting, Dr. Ooi, Dr. Rohani, Dr. Dalina, Amin Lotfi, Ahmad Fikri, Nurulaizan, Nur Fasihah, for their personal and scholarly interaction. Nice knowing all of you and thanks. Last but not least, my special thanks to my parents and families for their endless care, love and supports.

TABLE OF CONTENTS

	Page
ACKNOWLEDGEMENT	ii
TABLE OF CONTENTS	iii
LIST OF TABLES	ix
LIST OF FIGURES	xi
LIST OF ABBREVIATIONS	xix
LIST OF SYMBOLS	xxi
ABSTRAK	xxii
ABSTRACT	xxiv
CHAPTER ONE: INTRODUCTION	
1.1. Background	1
1.2. Problem statement	4
1.3. Research objectives	5
1.4. Thesis outlines	5
CHAPTER TWO: LITERATURE REVIEW	
2.1. Non-degradable synthetic polymer/biodegradable polymer blend	7
2.1.1. Linear low-density polyethylene (LLDPE)	7

2.1.2. Polyvinyl alcohol (PVOH)	8
2.1.3. Linear low-density polyethylene/polyvinyl alcohol (LLDPE/PVOH) blends and composites	9
2.2. Natural fibers filled polymer composites	11
2.2.1. Characteristic of natural fibers	11
2.2.2. Kenaf fiber	15
2.3. Kenaf-based polymer composites	19
2.3.1. Introduction	19
2.3.2. Chemically-treated kenaf-based polymer composites	20
2.4. Degradation	25
2.4.1. Introduction	25
2.4.2. Natural weathering	26
2.4.3. Soil burial	30

CHAPTER THREE: MATERIALS AND METHODOLOGY

3.1. Materials	33
3.1.1. Linear low density polyethylene	33
3.1.2. Polyvinyl alcohol	33
3.1.3. Kenaf bast fiber	34
3.1.4. Silane coupling agent: 3-(trimethoxysilyl)propyl methacrylate	34
3.1.5. Epichlorohydrin	34
3.1.6. Sodium hydroxide	35
3.1.7. Chromium (III) sulfate	35
3.1.8. Lysine	36
3.2. Filler treatments	36

3.2.1. Silane coupling agent	36
3.2.2. Glycidyl ester of fatty acid as eco-friendly coupling agent (EFCA)	37
3.2.3. Chromium (III) sulfate treatment	37
3.2.4. Lysine treatment	37
3.3. Fabrication of composites	38
3.3.1. Melt-mixing process	38
3.3.2. Compression moulding	38
3.4. Measurement and analysis	38
3.4.1. Tensile properties	38
3.4.2. Fourier transform infrared spectroscopy (FTIR)	39
3.4.3. Morphological study	39
3.4.4. Thermogravimetry analysis (TGA)	40
3.4.5. Differential scanning calorimetry (DSC)	40
3.4.6. Water absorption	41
3.4.7. Weight loss	41
3.5. Degradation Tests	42
3.5.1. Natural weathering	42
3.5.2. Soil burial	42

CHAPTER FOUR: RESULTS AND DISCUSSION

4.1. Linear low-density polyethylene/poly (vinyl alcohol)/kenaf bast fiber (LLDPE/PVOH/KNF) composites: effect of KNF loading	49
4.1.1. Processing characteristics	54
4.1.2. Tensile properties	57

4.1.3. Fourier transform infrared (FTIR) analysis	59
4.1.4. Morphological studies	
4.1.5. Thermogravimetric analysis (TGA)	59
4.1.6. Water absorption	65
4.2. Effect of natural weathering on properties of LLDPE/PVOH/KNF composites at different KNF loading	67 69
4.2.1. Tensile properties	72
4.2.2. Fourier transform infrared (FTIR) analysis	74
4.2.3. Morphological studies	
4.2.4. Differential scanning calorimetry (DSC)	74
4.2.5. Weight Loss	79
4.3. Effect of soil burial on properties of LLDPE/PVOH/KNF composites at different KNF loading	80 82
4.3.1. Tensile properties	85
4.3.2. Fourier transform infrared (FTIR) analysis	86
4.3.3. Morphological studies	
4.3.4. Differential scanning calorimetry (DSC)	
4.3.5. Weight loss	86
4.4. Linear low-density polyethylene/Poly (vinyl alcohol)/Kenaf (LLDPE/PVOH/KNF) Composites: Effect of 3-(trimethoxysilyl)propyl methacrylate (TMS) as Silane Coupling Agent	89 95 97
4.4.1. Processing characteristics	
4.4.2. Tensile properties	
4.4.3. Fourier transform infrared (FTIR) analysis	95
4.4.4. Morphological studies	97

4.4.5. Thermogravimetric analysis (TGA)	99
4.4.6. Water absorption	101
4.5. Linear low-density polyethylene/poly (vinyl alcohol)/kenaf bast fiber	104
(LLDPE/PVOH/KNF) Composites: effect of glycidyl ester of fatty acid as eco-friendly coupling agent (EFCA)	104
4.5.1. Processing characteristics	104
4.5.2. Tensile properties	106
4.5.3. Fourier transform infrared (FTIR) analysis	111
4.5.4. Morphological studies	113
4.5.5. Thermogravimetric analysis (TGA)	115
4.5.6. Water absorption	117
4.6. Linear low-density polyethylene/poly (vinyl alcohol)/kenaf bast fiber	119
(LLDPE/PVOH/KNF) Composites: effect of chromium (III) sulfate	
4.6.1. Processing characteristics	119
4.6.2. Tensile properties	122
4.6.3. Fourier transform infrared (FTIR) analysis	126
4.6.4. Morphological studies	128
4.6.5. Thermogravimetric analysis (TGA)	128
4.6.6. Water absorption	132
4.7. Linear low-density polyethylene/poly (vinyl alcohol)/kenaf bast fiber	134
(LLDPE/PVOH/KNF) composites: effect of lysine	
4.7.1. Processing characteristics	134
4.7.2. Tensile properties	136
4.7.3. Fourier transform infrared (FTIR) analysis	141
4.7.4. Morphological studies	142

4.7.5. Thermogravimetric analysis (TGA)	144
4.7.6. Water absorption	146

CHAPTER FIVE: CONCLUSIONS AND FUTURE WORK

5.1. Conclusions	149
5.2. Future recommendations	151

REFERENCES	153
-------------------	------------

LIST OF PUBLICATIONS

LIST OF TABLES

		Page
Table 2.1	Chemical composition of different constituents of kenaf fibers	16
Table 2.2	Mechanical properties and density values of selected natural (plant/ lignocellulosic) and synthetic fibers	17
Table 3.1	Properties of LLDPE by Lotte Chemical Titan	33
Table 3.2	Properties of PVOH by Sigma-Adrich Co.	33
Table 3.3	Technical specification of TMS by Sigma-Aldrich Co.	34
Table 3.4	Technical specification of C ₃ H ₅ ClO by Sigma-Adrich Co.	35
Table 3.5	Technical specification of NaOH by Sigma-Adrich Co.	35
Table 3.6	Technical specification of [Cr(H ₂ O) ₆] ₂ (SO ₄) ₃ .6(H ₂ O) by Sigma- Adrich Co.	35
Table 3.7	Technical specification of C ₆ H ₁₄ N ₂ O ₂ by Sigma-Adrich Co.	36
Table 4.1	TG-DTG parameters for LLDPE/PVOH/KNF composites with various KNF loadings	55
Table 4.2	Retention of tensile properties of LLDPE/PVOH/KNF composites with different KNF loadings after being subjected to weathering test for 3 and 6 months	65
Table 4.3	DSC results of LLDPE/PVOH/40 phr KNF composites before, after 3 and 6 months of natural weathering exposure	71
Table 4.4	Retention of tensile properties of LLDPE/PVOH/KNF composites with different KNF loadings after being subjected to soil burial test for 3 and 6 months	78
Table 4.5	DSC results of LLDPE/PVOH/KNF composites (at 40 phr KNF) before, after 3 and 6 months of soil burial exposure	85
Table 4.6	TG-DTG parameters of LLDPE/PVOH/KNF composites with untreated and TMS-treated KNF at 10 and 40 phr loadings	100

Table 4.7	TGA parameters of LLDPE/PVOH/KNF composites with untreated and EFCA-treated KNF at 10 and 40 phr KNF loadings	117
Table 4.8	TG-DTG parameters of LLDPE/PVOH/KNF composites with untreated and $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF at 10 and 40 phr loadings	131
Table 4.9	TGA parameters of LLDPE/PVOH/KNF composites with untreated and lysine-treated KNF at 10 and 40 phr KNF loadings	146

LIST OF FIGURES

		Page
Figure 2.1	Classification of natural fibers	11
Figure 2.5	Chemical structure of cellulose	13
Figure 2.3	Kenaf plant	15
Figure 2.4	Schematic synthesis of eco-friendly coupling agent, EFCA	24
Figure 3.1	Average temperature and rainfall data obtained from meteorology station in Butterworth (year 2017)	43
Figure 4.1	Processing torques of LLDPE/PVOH/KNF composites with different KNF loadings	45
Figure 4.2	Stabilization torques of LLDPE/PVOH/KNF composites with different KNF loadings	46
Figure 4.3	Tensile strength of LLDPE/PVOH/KNF composites with different KNF loadings	47
Figure 4.4	Tensile modulus of LLDPE/PVOH/KNF composites with different KNF loadings	48
Figure 4.5	Elongation at break of LLDPE/PVOH/KNF composites with different KNF loadings	49
Figure 4.6	FTIR spectra of LLDPE/PVOH/KNF composites with (a) 0 phr KNF (b) 10 phr KNF and (c) 40 phr KNF loadings	50
Figure 4.7	SEM micrographs of tensile fractured surfaces of LLDPE/PVOH/KNF composites with (a) 0 phr KNF (b) 10 phr KNF (c) 20 phr KNF and (d) 40 phr KNF loadings at magnification of 200x	52
Figure 4.8	TG thermograms of LLDPE/PVOH/KNF composites with different KNF loadings	54
Figure 4.9	DTG thermograms of LLDPE/PVOH/KNF composites with	55

	different KNF loadings	
Figure 4.10	Water absorption of LLDPE/PVOH/KNF composites with different KNF loadings	57
Figure 4.11	Equilibrium water absorption of LLDPE/PVOH/KNF composites With different KNF loadings	59
Figure 4.12	Tensile strength of LLDPE/PVOH/KNF composites at different KNF loadings before, and after subjected to natural weathering test for 3 and 6 months	61
Figure 4.13	Tensile modulus of LLDPE/PVOH/KNF composites at different KNF loadings before, and after subjected to natural weathering test for 3 and 6 months	63
Figure 4.14	Elongation at break of LLDPE/PVOH/KNF composites at different KNF loadings before, and after subjected to natural weathering test for 3 and 6 months	64
Figure 4.15	FTIR spectra of LLDPE/PVOH/KNF composites with (a) before (a)-(c) (0 month) (b) after 3 months and (c) after 6 months of natural weathering exposure	66
Figure 4.16	SEM micrographs of LLDPE/PVOH/KNF composites with (a) 0 (a)-(f) phr KNF (b) 10 phr KNF (c) 40 phr KNF after 3 months of weathering exposure and (d) 0 phr KNF (e) 10 phr KNF (f) 40 phr KNF after 6 months of weathering exposure at magnification of 1000X	68
Figure 4.17	DSC thermograms (melting) of LLDPE/PVOH/KNF composites before, after 3 and 6 months of natural weathering exposure	70
Figure 4.18	DSC thermograms (cooling) of LLDPE/PVOH/KNF composites before, after 3 and 6 months of natural weathering exposure	71
Figure 4.19	Weight loss of LLDPE/PVOH/KNF composites at different KNF	73

	loadings after subjected to natural weathering for 3 and 6 months	
Figure 4.20	Tensile strength of LLDPE/PVOH/KNF composites at different KNF loadings, before and after subjected to soil burial test for 3 and 6 months	75
Figure 4.21	Tensile modulus of LLDPE/PVOH/KNF composites with different KNF loadings, before and after subjected to soil burial test for 3 and 6 months	76
Figure 4.22	Elongation at break of LLDPE/PVOH/KNF composites with different KNF loadings after subjected to soil burial test for 3 and 6 months	78
Figure 4.23	FTIR spectra of LLDPE/PVOH/KNF composites (at 40 phr KNF) before, after 3 and 6 months of soil burial exposure	80
Figure 4.24	SEM micrographs of LLDPE/PVOH/KNF composites with (a) 0 (a)-(f) phr KNF (b) 10 phr KNF (c) 40 phr KNF after 3 months of soil burial exposure and (d) 0 phr KNF (e) 10 phr KNF (f) 40 phr KNF after 6 months of soil burial exposure at magnification of 1000X	81
Figure 4.25	DSC thermograms (melting) of LLDPE/PVOH/KNF composites (at 40 phr KNF) before, after 3 and 6 months of soil burial exposure	83
Figure 4.26	DSC thermograms (cooling) of LLDPE/PVOH/KNF composites (at 40 phr KNF) before, after 3 and 6 months of soil burial exposure	84
Figure 4.27	Weight loss of LLDPE/PVOH/KNF composites with different KNF loadings after subjected to soil burial for 3 and 6 months	86
Figure 4.28	Comparison of processing torque of LLDPE/PVOH/KNF composites with untreated and TMS-treated KNF at 10 and 40 phr KNF loading, respectively	87

Figure 4.29	Comparison of stabilization torque of LLDPE/PVOH/KNF composites with untreated and TMS-treated KNF at 10 and 40 phr KNF loading, respectively	88
Figure 4.30	Tensile strength of LLDPE/PVOH/KNF composites with untreated and TMS-treated KNF at different KNF loadings	89
Figure 4.31	Hydrolysis of TMS	91
Figure 4.32	Proposed possible interaction between TMS and KNF	91
Figure 4.33	Proposed possible interaction between TMS-treated KNF and PVOH	92
Figure 4.34	Proposed possible interaction between intermediate and LLDPE	92
Figure 4.35	Tensile modulus of LLDPE/PVOH/KNF composites with untreated and TMS-treated KNF at different KNF loadings	93
Figure 4.36	Elongation at break of LLDPE/PVOH/KNF composites with untreated and TMS-treated KNF at different KNF loadings	94
Figure 4.37	FTIR spectra of LLDPE/PVOH/KNF composites with (a) untreated and (b) TMS-treated KNF at 40 phr KNF loading	96
Figure 4.38	SEM micrographs of fractured surfaces of LLDPE/PVOH/KNF composites with (a) 10 phr untreated KNF (b) 10 phr TMS-treated KNF (c) 20 phr untreated KNF and (d) 20 phr TMS-treated KNF (e) 40 phr untreated KNF and (f) 40 phr TMS-treated KNF at magnification of 200x	98
Figure 4.39	TG thermograms of LLDPE/PVOH/KNF composites with untreated and TMS-treated KNF at 10 and 40 phr KNF loadings	99
Figure 4.40	DTG thermograms of LLDPE/PVOH/KNF composites with untreated and TMS-treated KNF at 10 and 40 phr KNF loadings	100
Figure 4.41	Water absorption of LLDPE/PVOH/KNF composites with untreated and TMS-treated KNF at 10 and 40 phr KNF loadings	102

Figure 4.42	Equilibrium water absorption of LLDPE/PVOH/KNF composites With untreated and TMS-treated KNF at 10 and 40 phr KNF loadings	103
Figure 4.43	Processing torque of LLDPE/PVOH/KNF composites with untreated and EFCA-treated KNF at 10 and 40 phr KNF loadings	104
Figure 4.44	Stabilization torque of LLDPE/PVOH/KNF composites with untreated and EFCA-treated KNF at 10 and 40 phr KNF loadings	105
Figure 4.45	Tensile strength of LLDPE/PVOH/KNF composites with untreated and EFCA-treated KNF at different KNF loadings	107
Figure 4.46	Proposed possible mechanism during pre-treatment of KNF with EFCA	108
Figure 4.47	Proposed possible mechanism between EFCA-treated KNF, PVOH and LLDPE	108
Figure 4.48	Tensile modulus of LLDPE/PVOH/KNF composites with untreated and EFCA-treated KNF at different KNF loadings	109
Figure 4.49	Elongation at break of LLDPE/PVOH/KNF composites with untreated and EFCA-treated KNF at different KNF loadings	111
Figure 4.50	FTIR spectra of LLDPE/PVOH/KNF composites with (a)-(b) (a) 40 phr untreated and (b) 40 phr EFCA-treated KNF	112
Figure 4.51	SEM micrographs of fractured surfaces of LLDPE/PVOH/KNF (a)-(f) composites with (a) 10 phr untreated KNF (b) 10 phr EFCA-treated KNF (c) 20 phr untreated KNF and (d) 20 phr EFCA-treated KNF (e) 40 phr untreated KNF and (f) 40 phr EFCA-treated KNF at magnification of 200x	114
Figure 4.52	TG thermograms of LLDPE/PVOH/KNF composites with untreated and EFCA-treated KNF at 10 and 40 phr KNF loadings	115
Figure 4.53	DTG thermograms of LLDPE/PVOH/KNF composites with	116

	untreated and EFCA-treated KNF at 10 and 40 phr KNF loadings	
Figure 4.54	Water absorption of LLDPE/PVOH/KNF composites with untreated and EFCA-treated KNF at 10 and 40 phr KNF loadings	118
Figure 4.55	Equilibrium water absorption of LLDPE/PVOH/KNF composites with untreated and EFCA-treated KNF at 10 and 40 phr KNF loadings	119
Figure 4.56	Processing torque of LLDPE/PVOH/KNF composites with untreated and $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF at 10 and 40 phr KNF loadings	120
Figure 4.57	Comparison of stabilization torque of LLDPE/PVOH/KNF composites with untreated and $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF at 10 and 40 phr KNF loadings	121
Figure 4.58	Tensile strength of LLDPE/PVOH/KNF composites with untreated and $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF at different KNF loadings	122
Figure 4.59	Proposed possible reactions that occurred during $\text{Cr}_2(\text{SO}_4)_3$ Treatment of KNF	123
Figure 4.60	Tensile modulus of LLDPE/PVOH/KNF composites with untreated and $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF at different KNF loadings	124
Figure 4.61	Elongation at break of LLDPE/PVOH/KNF composites with untreated and $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF at different KNF loadings	126
Figure 4.62	FTIR spectra of LLDPE/PVOH/KNF composites with (a) 40 phr (a)-(b) untreated and (b) 40 phr $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF	127
Figure 4.63	SEM micrographs of fractured surfaces of LLDPE/PVOH/KNF composites with (a) 10 phr untreated KNF (b) 10 phr $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF (c) 20 phr untreated KNF (d) 20 phr $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF (e) 40 phr untreated KNF and (f) 40 phr $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF at magnification of 200x	129

Figure 4.64	TG thermograms of LLDPE/PVOHKNF composites with untreated and $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF at 10 and 40 phr KNF loadings	130
Figure 4.65	DTG thermograms of LLDPE/PVOH/KNF composites with untreated and $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF at 10 and 40 phr KNF loadings	131
Figure 4.66	Water absorption of LLDPE/PVOH/KNF composites with untreated and $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF at 10 and 40 phr KNF loadings	132
Figure 4.67	Equilibrium water absorption of LLDPE/PVOH/KNF composites with untreated and $\text{Cr}_2(\text{SO}_4)_3$ -treated KNF at 10 and 40 phr KNF loadings	133
Figure 4.68	Processing torques of LLDPE/PVOH/KNF composites with untreated and lysine-treated KNF at 10 and 40 phr KNF loadings	134
Figure 4.69	Stabilization torques of LLDPE/PVOH/KNF composites with untreated and lysine-treated KNF at 10 and 40 phr KNF loadings	135
Figure 4.70	Tensile strength of LLDPE/PVOH/KNF composites with untreated and lysine-treated KNF at different KNF loadings	137
Figure 4.71	Proposed possible reaction between KNF and lysine	138
Figure 4.72	Proposed possible reaction between lysine-treated KNF and LLDPE/PVOH matrices	138
Figure 4.73	Tensile modulus of LLDPE/PVOH/KNF composites with untreated and lysine-treated KNF at different KNF loadings	139
Figure 4.74	Elongation at break of LLDPE/PVOH/KNF composites with untreated and lysine-treated KNF at different KNF loadings	140
Figure 4.75	FTIR spectra of LLDPE/PVOH/KNF composites with (a) 40 phr untreated and (b) 40 phr lysine-treated KNF	141
Figure 4.76	SEM micrographs of fractured surfaces of LLDPE/PVOH/KNF	143

(a)-(f)	composites with (a) 10 phr untreated KNF (b) 10 phr lysine-treated KNF (c) 20 phr untreated KNF (d) 20 phr lysine-treated KNF (e) 40 phr untreated KNF and (f) 40 phr lysine treated KNF at magnification of 200x	
Figure 4.77	TG thermograms of LLDPE/PVOH/KNF composites with untreated and lysine-treated KNF at 10 and 40 phr KNF loadings	145
Figure 4.78	DTG thermograms of LLDPE/PVOH/KNF composites with untreated and lysine-treated KNF at 10 and 40 phr KNF loadings	146
Figure 4.79	Water absorption of LLDPE/PVOH/KNF composites with untreated and lysine-treated KNF at 10 and 40 phr KNF loadings	147
Figure 4.80	Equilibrium water absorption of LLDPE/PVOH/KNF composites with untreated and lysine-treated KNF at 10 and 40 phr KNF loadings	148

LIST OF ABBREVIATIONS

AFTA	ASEAN Free Trade Area
APTES	3-aminopropyltriethoxysilane
ASTM	American Society for Testing and Materials
COCA	Coconut oil coupling agent
DSC	Differential Scanning Calorimetry
DTG	Derivative thermogravimetric
EFCA	Eco-friendly coupling agent
EVA	Ethylene vinyl acetate
FESEM	field emission scanning electron microscope
FTIR	Fourier transform infrared
HDPE	High density polyethylene
KCF	Kenaf core fiber
KNF	Kenaf bast fiber
KF	Kenaf fiber
KP	Kenaf powder
LDPE	Low density polyethylene
LLDPE	Linear low density polyethylene
MAPE	Maleated polyethylene
NaHCO ₃	Sodium hydrogen carbonate
NaOH	Sodium hydroxide
NKTB	National Kenaf and Tobacco Board
NR	Natural rubber
PA	Phthalic anhydride
PALF	Pineapple leaf fiber
PE	Polyethylene

PE-g-MA	Polyethylene-grafted maleic anhydride
PLA	Poly (lactic acid)
pMDI	Polymeric methylene diphenyl diisocyanate
PP	Polypropylene
PSP	Peanut shell powder
PU	Polyurethane
PVC	Poly (vinyl chloride)
PVOH	Poly (vinyl alcohol)
rHDPE	Recycled high-density polyethylene
rPP	Recycled polypropylene
SEM	Scanning Electron Microscopy
SS	Sago starch
TGA	Thermogravimetric analysis
TMS	3-3-(trimethoxysilyl)propyl methacrylate
TPSS	Thermoplastic sago starch
UV	Ultra-violet
WMCF	Waste maize cob flour
WTD	Waste tire dust

LIST OF SYMBOLS

E_b	Elongation at break
Kg	Kilogram
cm^3	Centimetre cube
rpm	Revolutions per minute
phr	Parts per hundred resin
wt. %	weight percent
MPa	MegaPascal
$^{\circ}\text{C}$	Degree celcius
mm	Millimetre
μm	Micrometer
N/m	Newton per metre
mW	Miliwatt
ΔH_f	Heat of fusion
T_m	Melting temperature
T_c	Crystallization temperature
%	Percentage
X_c	Degree of crystallinity
J/g	Joule per gram
$T_{5\%}$	Temperature at 5% weight loss
$T_{50\%}$	Temperature at 50% weight loss
W_t	Total water absorption (in weight)
W_1	Weight of specimen before immersion
W_2	Weight of specimen after immersion
W_b	Weight of sample before degradation test
W_a	Weight of sample after degradation test

**KESERASIAN DAN KEBOLEHDEGRADASI KOMPOSIT POLIETILENA
BERKETUMPATAN RENDAH LINEAR/POLIVINIL ALKOHOL TERISI
KENAF**

ABSTRAK

Penyelidikan berkaitan komposit polimer gentian semula jadi sedang meningkat dengan cepat disebabkan permintaan tinggi pada produk polimer yang mesra alam dengan harga yang berpatutan. Usaha-usaha yang berterusan adalah tertumpu untuk meningkatkan sifat-sifat komposit ini. Di dalam kajian ini, adunan polietilena berketumpatan rendah linear (LLDPE)/polivinil alkohol (PVOH) telah digunakan sebagai matrik polimer dengan komposisi yang telah ditetapkan pada 60/40 (wt. %), manakala gentian kenaf bast (KNF) digunakan sebagai pengisi. Kesan pembebanan pengisi dan pelbagai rawatan kimia terhadap pengisi semula jadi tersebut ke atas ciri-ciri pemprosesan, sifat-sifat tensil, struktur, morfologi, termal dan biodegradasi komposit LLDPE/PVOH/KNF telah dikaji. Komposit LLDPE/PVOH/KNF mengandungi pembebanan KNF yang berbeza (0, 10, 20, 30 and 40 phr) telah disediakan menggunakan pencampuran leburan dan pengacuanan mampatan. Didapati bahawa peningkatan pembebanan KNF, tork pemprosesan, modulus tensil, kestabilan termal dan penyerapan air komposit telah meningkat. Walau bagaimanapun, kekuatan tensil dan pemanjangan pada takat putus komposit telah didapati menurun. Ini menunjukkan lekatan antara muka yang lemah di antara matrik LLDPE/PVOH dan KNF sebagaimana dibuktikan dalam kajian SEM. Pencucuan semula jadi dan penanaman di dalam tanah telah memberikan kesan negatif kepada sifat-sifat komposit LLDPE/PVOH/KNF, sebagaimana ditunjukkan oleh

kemerosotan di dalam sifat-sifat tensil, kerusakan permukaan yang terdedah, dan peratusan kehilangan berat yang lebih tinggi. Seterusnya, keputusan daripada spektra FTIR mengesahkan kehadiran degradasi dengan kemunculan puncak karbonil yang jelas. Kehadiran perawatan kimia ke atas KNF telah meningkatkan sifat-sifat tensil, morfologi, sifat terma dan juga mengurangkan penyerapan air komposit LLDPE/PVOH/KNF. Perawatan kimia KNF telah disahkan melalui spektroskopi FTIR. Berdasarkan keputusan yang diperolehi, didapati penambahan KNF terawat 3-(trimetosisilil)propil metakrilat (TMS) ke dalam matrik LLDPE/PVOH telah meningkatkan tork pemprosesan, kekuatan tensil, modulus tensil, kestabilan terma dan mengurangkan penyerapan air komposit. Ini dibuktikan dengan peningkatan lekatan antara muka di antara KNF terawat TMS dan matrik LLDPE/PVOH melalui analisis SEM. Penambahan KNF terawat dengan agen pengkupel mesra alam (EFCA), kromium (III) sulfat dan lisin ke dalam matrik LLDPE/PVOH juga didapati meningkatkan tork pemprosesan, sifat-sifat tensil, kestabilan terma dan mengurangkan penyerapan air komposit. Keputusan daripada analisis SEM menunjukkan peningkatan di dalam lekatan antara muka di antara KNF terawat dan matrik LLDPE/PVOH. Keputusan FTIR juga mengesahkan pembentukan ikatan kimia di antara agen-agen pengkupel dan KNF, seterusnya menghasilkan pautan di antara KNF and matrik LLDPE/PVOH.