

**NUMERICAL ANALYSIS OF TBM TUNNEL BEHAVIOUR AND SUPPORT
UNDER HIGH STRESS ROCK MASSES IN PAHANG-SELANGOR RAW
WATER TRANSFER TUNNEL**

HEYAM HUSSEIN SHAALAN

UNIVERSITI SAINS MALAYSIA

2019

**NUMERICAL ANALYSIS OF TBM TUNNEL BEHAVIOUR AND SUPPORT
UNDER HIGH STRESS ROCK MASSES IN PAHANG-SELANGOR RAW
WATER TRANSFER TUNNEL**

by

HEYAM HUSSEIN SHAALAN

**Thesis submitted in fulfillment of the
requirements for the degree of
Doctor of Philosophy**

March 2019

ACKNOWLEDGEMENT

First of all, I would like to express my deepest appreciation to Assc. Prof. Dr. Mohd Ashraf Mohamad Ismail, my supervisor for his excellent guidance and advices throughout the process of this study. He helped me to improve my skills and permanently provided me with precious guidance, recommendations and suggestions.

I would like to thank the School of Civil Engineering, University Sains Malayisa, for providing me with the easy access of Rocscience and Plaxis Programs. I want also to thank Mr. Ahmad Halmi, Mr. Abdul Muluk Tajudin, Mr. Mohd Mazlan Kamis and also all the friendly staff in the School of Civil Engineering.

A deep gratitude I would like to present to Miss Lim Xiao Phin who has helped me with the software operation and installation. My special thank is extended to Mrs. Romziah Azit my schoolmate for her help to provide me with the required field data of my case study.

I would like to dedicate this thesis work to the memory of my father, Hussein Shaalan, I miss him every day. You left fingerprints of grace on our lives. You shan't be forgotten. Love, thanks and gratitude to my mother and brothers for all they have done for me throughout my life.

Furthermore, I want to thank my uncle Prof. Adil Hassan for his encouragement and support throughout my study in Malaysia. I have also to thank my lovely husband and best friend Marwan for been there when I need him. Last but important, my sweet, precious daughter, Zaynep, I dedicate this thesis work to you with love.

TABLE OF CONTENTS

| | Page |
|---|-------------|
| ACKNOWLEDGEMENT | ii |
| TABLE OF CONTENTS | iii |
| LIST OF TABLES | x |
| LIST OF FIGURES | xii |
| LIST OF ABBREVIATIONS | xxi |
| LIST OF SYMBOLS | xxii |
| ABSTRAK | xxvi |
| ABSTRACT | xxviii |
| CHAPTER ONE - INTRODUCTION | |
| 1.1 Background | 1 |
| 1.2 Problem Statement | 3 |
| 1.3 Objectives | 6 |
| 1.4 Scope of work | 8 |
| 1.5 Research Significance | 10 |
| 1.6 Thesis outline | 11 |
| CHAPTER TWO - LITERATURE REVIEW | |
| 2.1 Introduction | 13 |
| 2.2 Tunnelling under high overburden stresses | 15 |
| 2.2.1 In-situ stresses | 17 |

| | | |
|----------|---|----|
| 2.2.2 | In-situ stress measurement | 19 |
| 2.2.2(a) | Flat jack method | 21 |
| 2.2.2(b) | Overcoring method | 22 |
| 2.2.2(c) | Hydraulic fracturing | 23 |
| 2.2.3 | Constitutive models of rock mass | 25 |
| 2.2.3(a) | Generalized Hoek-Brown criterion | 26 |
| 2.2.3(b) | Mohr-Coulomb criterion | 31 |
| 2.3 | Granitic rock | 33 |
| 2.3.1 | Weathered profile of granitic rock | 34 |
| 2.4 | Rock brittle failure around tunnels | 36 |
| 2.4.1 | Overstressing in deep rock tunnels | 41 |
| 2.5 | Estimation of rock brittle failure around underground openings | 43 |
| 2.5.1 | Empirical approach | 43 |
| 2.5.2 | Numerical modelling of rock brittle failure | 45 |
| 2.6 | Stability of underground excavations in overstressing rock mass | 49 |
| 2.6.1 | Rock support systems | 51 |
| 2.6.2 | Estimating the required rock support | 51 |
| 2.6.2(a) | Rock quality designation index (RQD) | 52 |
| 2.6.2(b) | The RMR system | 52 |
| 2.6.2(c) | Rock tunnelling quality index, Q-system | 53 |
| 2.6.3 | Support systems for overstressed rock masses | 55 |
| 2.6.3(a) | Rock bolts | 58 |
| 2.6.3(b) | Wire mesh | 60 |
| 2.6.3(c) | Cable lacing | 61 |

| | | |
|----------|--|----|
| 2.6.3(d) | Shotcrete lining | 62 |
| 2.6.4 | Time-dependent behaviour of shotcrete material | 67 |
| 2.6.4(a) | Modelling the shotcrete lining behaviour | 68 |
| 2.6.5 | Shotcrete constitutive model | 71 |
| 2.6.5(a) | Introduction | 71 |
| 2.6.5(b) | Model formulation | 72 |
| 2.6.5(c) | Yield surfaces | 72 |
| 2.6.5(d) | Strain hardening/softening principles | 74 |
| 2.6.5(e) | Time dependent stiffness and strength | 76 |
| 2.6.5(f) | Creep and shrinkage | 79 |
| 2.7 | Summary | 80 |

CHAPTER THREE - RESEARCH METHODOLOGY

| | | |
|----------|---|-----|
| 3.1 | Introduction | 82 |
| 3.2 | Project description | 85 |
| 3.2.1 | Geological conditions of the study area | 86 |
| 3.2.2 | Field data investigation | 88 |
| 3.2.2(a) | Rock mass properties | 89 |
| 3.2.2(b) | In-situ stress measurements | 90 |
| 3.2.2(c) | Rock mass classification | 92 |
| 3.2.2(d) | Tunnel support system | 94 |
| 3.2.3 | Tunnelling in overstressing rock mass | 96 |
| 3.2.3(a) | Overstressing assessment | 98 |
| 3.3 | Numerical modelling | 100 |

| | | |
|----------|---|-----|
| 3.3.1 | Tunnel excavation process | 103 |
| 3.3.2 | Brittle failure simulation | 105 |
| 3.3.2(a) | Failure indicators | 106 |
| 3.3.3 | Influence of CSFH model strength parameters on the rock failure | 106 |
| 3.3.3(a) | Peak cohesion and friction angle | 107 |
| 3.3.3(b) | Residual cohesion and fiction angle | 108 |
| 3.3.3(c) | Dilation angle | 108 |
| 3.4 | Evaluation of the Tunnel Stability | 109 |
| 3.5 | Time-dependent behaviour of the TBM tunnel lining | 112 |
| 3.5.1 | Numerical modelling | 112 |
| 3.5.1(a) | Field stresses | 114 |
| 3.5.1(b) | Tunnel excavation process | 114 |
| 3.5.1(c) | Material parameters for the shotcrete model | 115 |
| 3.5.1(d) | Shotcrete model validation | 117 |
| 3.5.2 | Elastic and Elasto-plastic behaviour of the shotcrete lining | 118 |
| 3.5.3 | SFRS lining behaviour with time | 119 |
| 3.6 | Effect of the Shotcrete model parameters | 120 |
| 3.6.1 | Time-dependent strength parameter | 120 |
| 3.6.2 | Time-dependent stiffness parameter | 121 |
| 3.6.3 | Effect of creep and shrinkage | 121 |
| 3.6.4 | Steel fibre effect | 122 |
| 3.7 | Effect of tunnel parameters | 123 |
| 3.8 | Summary | 124 |

CHAPTER FOUR – RESULTS AND DISCUSSION

| | | |
|----------|--|-----|
| 4.1 | Introduction | 126 |
| 4.2 | Evaluation of the rock overstressing | 127 |
| 4.3 | Numerical modelling of the rock failure | 128 |
| 4.3.1 | Elastic analysis | 128 |
| 4.3.2 | Elastic- Perfectly plastic model | 130 |
| 4.3.3 | Elastic-Brittle plastic model with (residual friction $m_r = 0$ and residual cohesion $s_r = 0.11$) | 131 |
| 4.3.4 | Parametric analysis of the CSFH model parameters | 132 |
| 4.3.4(a) | Effect of the peak friction angle | 132 |
| 4.3.4(b) | Effect of the peak cohesion strength | 133 |
| 4.3.4(c) | Effect of the residual friction angle | 137 |
| 4.3.4(d) | Effect of the residual cohesion strength | 139 |
| 4.3.4(e) | Effect of the dilation angle | 141 |
| 4.3.4(f) | Optimized input parameters for the CSFH model | 143 |
| 4.4 | Stability evaluation of the TBM tunnel | 149 |
| 4.4.1 | Effect of the lining thickness | 149 |
| 4.4.2 | Effect of the tunnel size | 151 |
| 4.4.3 | Effect of fallout removal or scaling | 154 |
| 4.4.4 | Effect of the tunnel overburden | 158 |
| 4.4.5 | Summary | 164 |
| 4.5 | Numerical analysis of the TBM-2 tunnel lining | 165 |
| 4.5.1 | Model validation | 166 |

| | | |
|---|--|-----|
| 4.5.2 | Comparison study between the shotcrete model and elastic analysis | 167 |
| 4.6 | Time-dependent behaviour of the SFRS lining | 170 |
| 4.6.1 | Compressive strength of the SFRS lining | 170 |
| 4.6.2 | Elastic stiffness of the SFRS lining | 172 |
| 4.6.3 | Stresses of the SFRS lining | 174 |
| 4.6.4 | Vertical displacement in the SFRS lining | 179 |
| 4.7 | Effect of the shotcrete model input parameters | 183 |
| 4.7.1 | Time-dependent strength parameter | 183 |
| 4.7.2 | Time-dependent stiffness parameter | 185 |
| 4.7.3 | Effect of creep and shrinkage | 186 |
| 4.7.4 | Steel fibre effect | 190 |
| 4.8 | Effect of tunnel parameters | 194 |
| 4.8.1 | Effect of SFRS lining thickness | 194 |
| 4.8.2 | Effect of tunnel diameter | 200 |
| 4.9 | Summary | 205 |
| CHAPTER FIVE - CONCLUSION AND RECOMMENDATION | | |
| 5.1 | Conclusion | 208 |
| 5.2 | Recommendation for future works | 214 |
| REFERENCES | | 215 |
| APPENDICES | | |
| APPENDIX A: | Steps for calculation RQD (Deere, 1989) | |
| APPENDIX B: | Rock Mass Rating System (After Bieniawski, 1989). | |
| APPENDIX C: | Guidelines for excavation and support of 10 m span rock tunnels according to the RMR system (After Bieniawsk 1989) | |

- APPENDIX D: Classification of individual parameters used in the Tunnelling Quality Index Q (Barton et al, 1974)
- APPENDIX E: Geological mapping for case 1
- APPENDIX F: Geological mapping for case 2
- APPENDIX G: Geological mapping for case 3
- APPENDIX H: Analysis of rock strength using ROCKLAB for the case 1
- APPENDIX I: Analysis of rock strength using ROCKLAB for the case 2
- APPENDIX J: Analysis of rock strength using ROCKLAB for the case 3
- APPENDIX K: Shotcrete early strength classes according to EN 14487 (2006)

LIST OF PUBLICATIONS

LIST OF TABLES

| | | Page |
|------------|--|-------------|
| Table 2.1 | Guidelines for estimating disturbance factor D | 27 |
| Table 2.2 | Examples of rock overstressing (Brox, 2013) | 42 |
| Table 2.3 | ESR values (Barton et al. 1974) | 55 |
| Table 2.4 | Advantages and disadvantages of shotcrete dry process | 66 |
| Table 2.5 | Advantages and disadvantages of shotcrete wet process | 66 |
| Table 3.1 | Critical cases of TBM-2 section used for the research study | 89 |
| Table 3.2 | Rock compressive strength from overcoring test | 89 |
| Table 3.3 | Rock mass properties from the Schmidt hammer test | 89 |
| Table 3.4 | Summary of in-situ stress test | 91 |
| Table 3.5 | JH rock mass classes (after Azit and Ismail, 2014) | 93 |
| Table 3.6 | Steel fibre shotcrete mix proportion | 95 |
| Table 3.7 | Site results of the SFRS compressive strength | 95 |
| Table 3.8 | Steel fibre reinforced shotcrete lining properties | 95 |
| Table 3.9 | Summary of the critical cases with the site observed failure details | 98 |
| Table 3.10 | Rock overstressing classification (Hoek and Marinos, 2009) | 100 |
| Table 3.11 | Input parameters of the numerical modelling | 102 |

| | | |
|------------|---|-----|
| Table 3.12 | Parameters values for the stability analysis | 110 |
| Table 3.13 | Tunnel depths for the stability analysis | 111 |
| Table 3.14 | Input parameters for the equivalent Mohr-Coulomb model | 113 |
| Table 3.15 | Shotcrete model input parameters for the SFRS lining | 116 |
| Table 3.16 | Input parameters of the shotcrete model of the concrete lining | 118 |
| Table 3.17 | Shotcrete model parameters for the unreinforced tunnel lining | 123 |
| Table 4.1 | Rock failure classification | 127 |
| Table 4.2 | Simulated failure depth using the elastic-perfectly-plastic model | 130 |
| Table 4.3 | Simulated failure depth using the Elastic-Brittle-plastic model with $m_r = 0$ and $S_r = 0.11$ | 131 |
| Table 4.4 | Summary of the significance of CSFH model parametric study | 143 |
| Table 4.5 | Strength parameters of CSFH model | 144 |
| Table 4.6 | Summary of the parametric study significance | 164 |

LIST OF FIGURES

| | | Page |
|-------------|--|-------------|
| Figure 2.1 | Tunnel instability and brittle failure as a function of rock mass strength and in- situ stress (Hoek et al., 1995) | 15 |
| Figure 2.2 | The three principal stresses σ_1 , σ_2 and σ_3 induced in an element of rock close to a horizontal tunnel subjected to a vertical in- situ stress σ_v , a horizontal in situ stress σ_{h1} in a plane normal to the tunnel axis and a horizontal in situ stress σ_{h2} parallel to the tunnel axis. (Hoek et al. 1995) | 18 |
| Figure 2.3 | Principal stress directions in the rock surrounding a horizontal tunnel subjected to a horizontal in situ stress σ_{h1} equal to 3 σ_v , where σ_v is the vertical in situ stress (Hoek et al. 1995) | 18 |
| Figure 2.4 | Schematic Diagram of (a) Flat Jack, (b) Test Configuration | 22 |
| Figure 2.5 | General steps in overcoring clarified by the Borre probe (Hakala et al., 2003) | 23 |
| Figure 2.6 | hydraulic fracturing principles | 24 |
| Figure 2.7 | General chart for GSI estimates from the geological observations | 28 |
| Figure 2.8 | Failure zone observed around a circular test tunnel. The micro-seismic events locations in the notch area (+), and acoustic emission locations (-) in the tensile failure zone (after Read 1994). | 37 |
| Figure 2.9 | Stability classification developed for square tunnels in South Africa modified by Martin et al., (1999) from the field observations of Hoek and Brown (1980) | 40 |
| Figure 2.10 | Severe overstressing of 1700m deep tunnel (Brox, 2013) | 42 |
| Figure 2.11 | Failure depth as a function of $(\sigma_{\theta_{max}} / \sigma_{ci})$ modified by Martin et al. (1999) | 44 |
| Figure 2.12 | Strength envelopes representing by the spalling failure parameters and the simulated breakout zone at the Mine-by tunnel (Diederichs, 2007). | 48 |

| | | |
|-------------|---|----|
| Figure 2.13 | V-notch zone created by scaling in the Kristineberg mine (Edelbro and Sandström 2009) | 50 |
| Figure 2.14 | Steps for calculation <i>RQD</i> (Deere, 1989) | 53 |
| Figure 2.15 | Estimated rock support according to the tunnelling quality index <i>Q</i> (After Grimstad and Barton, 1993) | 55 |
| Figure 2.16 | Cable lacing in a hard rock mass in Chile to reduce damage from brittle failure (Hoek and Marinos 2009). | 57 |
| Figure 2.17 | Steel sets Installed directly behind the TBM shield in the Olmos tunnel in Peru (Hoek and Marinos, 2009) | 58 |
| Figure 2.18 | Adjust of a single block and systematic bolting (Palmstöm and Nilsen, 2000) | 59 |
| Figure 2.19 | Chain linked, single braided wire mesh, left, and welded wire mesh, right (Hoek et al. 1995). | 61 |
| Figure 2.20 | Wire mesh to support failure zone (Hjálmarsson, 2011) | 61 |
| Figure 2.21 | Dry-mix shotcrete technology (after Austin & Robins, 1995) | 65 |
| Figure 2.22 | Wet-mix shotcrete process (after Austin & Robins, 1995) | 65 |
| Figure 2.23 | Yield surfaces and failure envelope of the mode (Schädlich and Schweiger, 2014b) | 73 |
| Figure 2.24 | Stress - strain curve in compression (Schädlich and Schweiger, 2014b) | 75 |
| Figure 2.25 | Shotcrete model tension behaviour (Schädlich and Schweiger, 2014b) | 76 |
| Figure 2.26 | Evaluation of shotcrete stiffness with time (Schädlich and Schweiger, 2014b) | 77 |
| Figure 2.27 | Evaluation of shotcrete strength with time (Schädlich and Schweiger, 2014b) | 78 |
| Figure 3.1 | Research methodology flowchart | 84 |
| Figure 3.2 | Tunnel structure of Pahang-Selangor Raw Water Transfer tunnel (after Azit and Ismail, 2016 b) | 85 |
| Figure 3.3 | Geological profiles along the tunnel and TBM excavation location (MEGTW, 2014) | 87 |

| | | |
|-------------|---|-----|
| Figure 3.4 | Geological condition along the tunnel alignment (after Azit and Ismail, 2016 a) | 87 |
| Figure 3.5 | Grain size and quartz contents of Main Range Granite (MEGTW, 2014) | 88 |
| Figure 3.6 | Location of the study cases | 88 |
| Figure 3.7 | In-situ stress test locations in Pahang-Selangor Water Transfer Tunnel (after Azit et al., 2015) | 91 |
| Figure 3.8 | Schmidt net projection of principal stress (after Azit et al., 2015) | 91 |
| Figure 3.9 | JH classification for rock mass classes (after Azit and Ismail, 2014) | 93 |
| Figure 3.10 | Percentage of total rock classes | 94 |
| Figure 3.11 | Rock spalling in Pahang-Selangor water transfer tunnel (after Azit and Ismail, 2016 b) | 97 |
| Figure 3.12 | Stress-induced fractures that developed at tunnel sidewalls (after Kawata et al., 2014) | 97 |
| Figure 3.13 | Geometrical model and meshing around the tunnel | 102 |
| Figure 3.14 | Progressive development of the rock stress by the load split method | 104 |
| Figure 3.15 | Flowchart of the tunnel stability evaluation | 111 |
| Figure 3.16 | Yield elements failed in shear, dashed line indicates the scaled notch | 111 |
| Figure 3.17 | (a) Geometric model, (b) Mesh around the tunnel | 113 |
| Figure 3.18 | Schematic representation of β -method for the analysis of TBM tunnel | 115 |
| Figure 4.1 | Strength factor of elastic analysis model for the three cases | 129 |
| Figure 4.2 | Yield elements failed in the shear of the elastic-perfectly-plastic | 130 |
| Figure 4.3 | Yield elements failed in the shear of the elastic-brittle-plastic model with $m_r = 0$ and $S_r = 0.11$ | 131 |
| Figure 4.4 | Effect of the peak friction angle on the simulated failure zone for the Case 1 (Ch. 23048m) | 133 |

| | | |
|-------------|--|-----|
| Figure 4.5 | Effect of the peak friction angle on the simulated failure zone for the Case 2 (Ch. 23732m) | 133 |
| Figure 4.6 | Effect of the peak friction angle on the simulated failure zone for the Case 3 (Ch. 23048m) | 134 |
| Figure 4.7 | Effect of the peak friction angle on the failure depth for the three critical cases | 134 |
| Figure 4.8 | Effect of the peak cohesion strength on the simulated failure zone for the Case 1 (Ch. 23048m) | 135 |
| Figure 4.9 | Effect of the peak cohesion strength on the simulated failure zone for the Case 2 (Ch. 23732m) | 136 |
| Figure 4.10 | Effect of the peak cohesion strength on the simulated failure zone for the Case 3 (Ch. 23742m) | 136 |
| Figure 4.11 | Effect of the peak cohesion strength on the failure depth | 137 |
| Figure 4.12 | Effect of the variation in the residual friction angle for the Case 1 | 138 |
| Figure 4.13 | Effect of the variation in the residual friction angle for the Case 2 | 138 |
| Figure 4.14 | Effect of the variation in the residual friction angle for the Case 3 | 138 |
| Figure 4.15 | Effect of residual friction angle on the failure depth | 139 |
| Figure 4.16 | Influence of different residual cohesion strength values on the yield elements that failed in the shear for the case 1 | 140 |
| Figure 4.17 | Influence of different residual cohesion strength values on the yield elements that failed in the shear for the case 2 | 140 |
| Figure 4.18 | Influence of different residual cohesion strength values on the yield elements that failed in the shear for the case 3 | 140 |
| Figure 4.19 | Effect of the residual cohesion on the failure depth | 141 |
| Figure 4.20 | Variation in the dilation angle and its influence on the failure depth and extension for the Case 1 | 142 |
| Figure 4.21 | Variation in the dilation angle and its influence on the failure depth and extension for the Case 2 | 142 |
| Figure 4.22 | Variation in the dilation angle and its influence on the failure depth and extension for the Case 3 | 142 |

| | | |
|-------------|---|-----|
| Figure 4.23 | Effect of the dilation angle on the failure depth | 143 |
| Figure 4.24 | Simulated failure zone of the tunnel sides utilising the CSFH model | 144 |
| Figure 4.25 | Peak and residual strength envelopes of the rock utilising the CSFH model for Case 1 | 145 |
| Figure 4.26 | Peak and residual strength envelopes of the rock utilising the CSFH model for Case 2 | 146 |
| Figure 4.27 | Peak and residual strength envelopes of the rock utilising the CSFH model for Case 3 | 147 |
| Figure 4.28 | Comparison between the actual and the simulated failure depth | 148 |
| Figure 4.29 | Average increase in the failure depth for the three cases | 148 |
| Figure 4.30 | Effect of SFRS lining thickness on the depth of the failure for the Case 1 | 150 |
| Figure 4.31 | Effect of SFRS lining thickness on the depth of the failure for the Case 2 | 150 |
| Figure 4.32 | Effect of SFRS lining thickness on the depth of the failure for the Case 3 | 150 |
| Figure 4.33 | The relationship between failure depth and the SFRS lining thickness for the three cases | 151 |
| Figure 4.34 | Effect of tunnel diameter on the depth of failure for Case 1 | 152 |
| Figure 4.35 | Effect of tunnel diameter on the depth of failure for Case 2 | 152 |
| Figure 4.36 | Effect of tunnel diameter on the depth of failure for Case 3 | 152 |
| Figure 4.37 | The relationship between failure depth and the tunnel diameters | 153 |
| Figure 4.38 | Variation of tunnel diameter with the tangential stress at the tunnel sidewalls | 153 |
| Figure 4.39 | Variation of tunnel diameter with the total vertical displacement of surrounding rock mass | 154 |
| Figure 4.40 | Yield elements failed in shear for the gradual removal of the failure region for the Case 1 | 155 |

| | | |
|-------------|--|-----|
| Figure 4.41 | Yield elements failed in shear for the gradual removal of the failure region for the Case 2 | 155 |
| Figure 4.42 | Yield elements failed in shear for the gradual removal of the failure region for the Case 2 | 155 |
| Figure 4.43 | Major principal stress σ_1 distribution for the gradual removal of the failure region for Case 1 | 156 |
| Figure 4.44 | Major principal stress σ_1 distribution for the gradual removal of the failure region for Case 2 | 157 |
| Figure 4.45 | Major principal stress σ_1 distribution for the gradual removal of the failure region for Case 3 | 158 |
| Figure 4.46 | Distribution of yield elements failure in shear for each case at different depths for Case 1 | 160 |
| Figure 4.47 | Distribution of yield elements failure in shear for each case at different depths for Case 2 | 160 |
| Figure 4.48 | Distribution of yield elements failure in shear for each case at different depths for Case 3 | 160 |
| Figure 4.49 | Effect of tunnel overburden on the rock failure depth | 161 |
| Figure 4.50 | Principal stress distribution around the tunnel at different depths for the Case 1 | 161 |
| Figure 4.51 | Principal stress distribution around the tunnel at different depths for the Case 2 | 162 |
| Figure 4.52 | Principal stress distribution around the tunnel at different depths for the Case 3 | 163 |
| Figure 4.53 | Effect of tunnel depth on the tangential stress at tunnel sidewall | 163 |
| Figure 4.54 | Effect of tunnel depth on the total vertical displacement of the rock mass | 164 |
| Figure 4.55 | Shotcrete model validation for concrete compressive strength with time from Al-Ameeri (2013) | 167 |
| Figure 4.56 | Distribution of major principal stress of the tunnel lining using (a) Shotcrete model and (b) Elastic analysis | 168 |
| Figure 4.57 | Major principal stress along the tunnel lining using the shotcrete model and the elastic analysis | 169 |

| | | |
|-------------|---|-----|
| Figure 4.58 | Distribution of the vertical displacement of the tunnel lining using (a) Shotcrete model and (b) Elastic analysis | 169 |
| Figure 4.59 | Vertical displacement along the tunnel lining using the shotcrete model and the elastic analysis | 170 |
| Figure 4.60 | Early strength of shotcrete with time at the first six hours | 172 |
| Figure 4.61 | Development of shotcrete compressive strength with time at 28 days | 172 |
| Figure 4.62 | Development of the shotcrete Stiffness with time in the first six hours | 173 |
| Figure 4.63 | Stiffness of the shotcrete lining with time at 28 days | 174 |
| Figure 4.64 | Distribution of the principal stresses along the tunnel lining at H = 1002m | 175 |
| Figure 4.65 | Distribution of the principal stresses along the tunnel lining at H = 700m | 176 |
| Figure 4.66 | Development of the lining stress with time for tunnel depth of 1002m | 176 |
| Figure 4.67 | Development of the lining stress with time for tunnel depth of 700m | 177 |
| Figure 4.68 | Development of the lining stress with time at tunnel crown | 178 |
| Figure 4.69 | Development of the lining stress with time at tunnel sidewall | 178 |
| Figure 4.70 | The relationship of the elastic stiffness and the stresses in SFRS lining with time | 179 |
| Figure 4.71 | Vertical displacement along the tunnel lining at H=1002m | 180 |
| Figure 4.72 | Vertical displacement along the tunnel lining at H=700m | 180 |
| Figure 4.73 | Development of the lining vertical displacement with time at tunnel depth of 1002m | 181 |
| Figure 4.74 | Development of the lining vertical displacement with time at tunnel depth of 700m | 181 |
| Figure 4.75 | Development of the lining displacement with time at tunnel crown | 182 |

| | | |
|-------------|--|-----|
| Figure 4.76 | Development of the lining displacement with time at tunnel sidewall | 183 |
| Figure 4.77 | Evaluation of shotcrete strength classes with time at 7 days | 184 |
| Figure 4.78 | Evaluation of shotcrete strength classes with time at 28 days | 185 |
| Figure 4.79 | Shotcrete elastic stiffness with time in 7 days | 186 |
| Figure 4.80 | Shotcrete elastic stiffness with time up to 28 days | 186 |
| Figure 4.81 | Effect of the creep and shrinkage strain on the lining tensile stress with time at the tunnel crown | 188 |
| Figure 4.82 | Effect of the creep and shrinkage strain on the lining compression stress with time at the tunnel sidewall | 188 |
| Figure 4.83 | Effect of creep and shrinkage strain on development of lining displacement with time at the tunnel crown | 189 |
| Figure 4.84 | Effect of creep and shrinkage strain on development of lining displacement with time at the tunnel sidewall | 189 |
| Figure 4.85 | The compressive strength of reinforced and unreinforced tunnel lining with time | 190 |
| Figure 4.86 | The elastic stiffness of reinforced and unreinforced tunnel lining with time | 191 |
| Figure 4.87 | Effect of steel fibre content on the development of lining stress with time at the tunnel crown | 192 |
| Figure 4.88 | Effect of steel fibre content on the development of lining stress with time at the tunnel side wall | 192 |
| Figure 4.89 | Effect of steel fibre parameters on the development of lining vertical displacement with time at the tunnel crown | 193 |
| Figure 4.90 | Effect of steel fibre parameters on the development of lining vertical displacement with time at the tunnel sidewall | 193 |
| Figure 4.91 | Stress distribution along the tunnel lining with different lining thicknesses | 195 |
| Figure 4.92 | Effect of lining thicknesses on the SRFS lining stresses with time at the tunnel crown | 197 |

| | | |
|--------------|--|-----|
| Figure 4.93 | Effect of lining thicknesses on the SRFS lining stresses with time at the tunnel sidewall | 197 |
| Figure 4.94 | Vertical displacement along the tunnel lining with different lining thicknesses | 198 |
| Figure 4.95 | Effect of lining thicknesses on the SRFS lining vertical displacement with time at the tunnel crown | 199 |
| Figure 4.96 | Effect of lining thicknesses on the SRFS lining vertical displacement with time at the tunnel sidewall | 199 |
| Figure 4.97 | Stress distribution along the tunnel lining using different tunnel diameters | 200 |
| Figure 4.98 | Effect of tunnel diameter on the SRFS lining stresses with time at the tunnel crown | 202 |
| Figure 4.99 | Effect of tunnel diameter on the SRFS lining stresses with time | 202 |
| Figure 4.100 | Vertical displacement along the tunnel lining using different tunnel diameters | 202 |
| Figure 4.101 | Effect of tunnel diameter on the SRFS lining vertical displacement with time at the tunnel crown | 204 |
| Figure 4.102 | Effect of tunnel diameter on the SRFS lining vertical displacement with time | 205 |

LIST OF ABBREVIATIONS

| | |
|---------------|---|
| TBM | Tunnel boring machine |
| CSFG | Cohesion-Softening Friction-Hardening |
| SFRS | Steel fibre reinforced shotcrete |
| 2D | Two dimensional |
| 3D | Three dimensional |
| WSM | The World Stress Map |
| Di | Damage index |
| URL | Underground research laboratory |
| SF | Safety factor |
| SWFS | Cohesion Weakening and Frictional Strengthening |
| UCS | Uniaxial compressive strength |
| HME | Hypothetical Modulus of Elasticity |
| ACI | American concrete institute |
| NATM | New Austrian tunnelling method |
| RQD | Rock Quality Designation |
| JH | Japan Highway Public Corporation |
| SCC | Self compacting concrete |
| J1, J2 and J3 | Early shotcrete strength classes |
| GSI | Geological Strength Index |

LIST OF SYMBOLS

| | |
|---------------|--|
| m, s | Hoek-Brown parameters |
| m_r | Residual friction |
| s_r | Residual cohesion |
| σ_v | Vertical stress |
| σ_{h1} | Maximum horizontal stress |
| σ_{h2} | Minimum horizontal stress |
| σ_1 | Major principal stress |
| σ_2 | Medium principal stress |
| σ_3 | Minimum principal stress |
| H | Tunnel depth |
| γ | Unit weight |
| k_0 | Coefficient of lateral stress |
| σ'_1 | Maximum effective stresses |
| σ'_3 | Minimum effective stresses at failure |
| σ_{ci} | Uniaxial compressive strength of the intact rock |
| m_b | Material constant |

| | |
|----------------------|---|
| m_i | Material constant for the intact rock |
| D | Degree of disturbance |
| c | Cohesive strength |
| ϕ | Angle of friction |
| τ | Shear strength |
| σ_n' | Normal stress |
| σ_t | Rock tensile strength |
| σ_{max} | Maximum tangential stress |
| ε | Total strain |
| ε^e | Elastic strain |
| ε^p | Plastic strain |
| ε^{cr} | Creep strain |
| ε^{shr} | Shrinkage strain |
| F_C | Mohr-Coulomb yield surface |
| F_t | Rankine yield surface in the tensile zone |
| f_{cy} | Uniaxial compressive yield stress |
| f_t | Tensile strength yield stress |
| H_C | Normalised strain hardening/softening parameter |
| ε_{cp}^p | Plastic peak strain in uniaxial compression |