



UGM UNIVERSITI
SAINS
MALAYSIA



OPTIMIZATION OF POWER FROM FOOD WASTE USING MEMBRANE-LESS MICROBIAL FUEL CELL

by

NADIRA ANANDITA

A dissertation submitted in the partial fulfilment of the requirements for the degree of
Bachelor of Technology (B.Tech) in the field of Bioprocess Technology
School of Industrial Technology Universiti Sains Malaysia

July 2020



**PUSAT PENGAJIAN TEKNOLOGI INDUSTRI
UNIVERSITI SAINS MALAYSIA**

**BORANG PENYERTAAN DISERTAI MUTAKHIR
SATU (1) NASKAH**

Nama Penyelia: DR. MUAZ MOHD ZAINI MAKHTAR


Bahagian: TEKNOLOGI BIOPROSES

Saya telah menyemak semua pembetulan/pindaan yang dilaksanakan oleh
~~Eneik/Puan/Cik~~ NADIRA ANANDITA

mengemui disertainya sebagaimana yang dipersetujui oleh Panel Pemeriksa di Viva
Vocanya.

2. Saya ingin mengesahkan bahawa saya berpuashati dengan pembetulan/pindaan
yang dilaksanakan oleh calon.

Sekian, terima kasih.


DR. MUAZ BIN MOHD ZAINI MAKHTAR
Senior Lecturer
Bioprocess Technology Division
School of Industrial Technology,
Universiti Sains Malaysia,
11800 Penang, Malaysia

(Tandatangan dan cop)

18 JUN 2020

Tarikh

DECLARATION BY AUTHOR

This dissertation is composed of my original work and contains no material previously published or written by another person except where due reference has been made in the text. The content of my dissertation is the result of work I have carried out since the commencement of my research project and does not include a substantial part of work that has been submitted to qualify for the award of any other degree or diploma in any university or other tertiary institution.

A handwritten signature in black ink, appearing to be 'Nadira Anandita', written in a cursive style. The signature is positioned above a horizontal line.

Nadira Anandita
June 2020

ACKNOWLEDGMENT

I would like to express my sincere appreciation and gratitude to my final year project Supervisor Dr Muaz Mohd Zaini Makhtar for his advice and guidance throughout this project. His commitment and passion for this project helps me to improve my skills and knowledge. Special thanks to Encik Asmaizan and Puan Najma for their help and guidance to carry out my lab work. Not to forget, my friend Mirza Faisal who is also under supervision Dr. Muaz, as well my Master student senior, Najib Ikmal who willing to lend hand and knowledge assisting throughout this study.

A massive thanks to all my classmates who give moral support and guidance in order to complete my project. Not to forget my fellow FYP mates who are willing to lend hand and support to finish this project. I also would to thanks the School of Industrial Technology for the facilities provided which do help me a lot to finish my project.

Last but not least, big thanks to my beloved parents for their huge sacrifice and support that encourage me to do this research project and throughout my study in Bachelor of Bioprocess Technology. Without them I might not be able to be where I am right now and this project as well as the degree is my little gift from me.

Nadira Anandita

June 2020

TABLE OF CONTENTS

| | Page |
|------------------------------------|------|
| ACKNOWLEDGEMENT | iv |
| TABLE OF CONTENTS | v |
| LIST OF TABLES | viii |
| LIST OF FIGURES | ix |
| LIST OF SYMBOLS | x |
| LIST OF ABBREVIATIONS | xi |
| ABSTRAK | xii |
| ABSTRACT | xiii |
| CHAPTER 1 INTRODUCTION | |
| 1.1 Research background | 1 |
| 1.2 Problem statement | 2 |
| 1.3 Research objectives | 3 |
| 1.4 Scope of work | 4 |
| 1.5 Thesis organization | 4 |
| CHAPTER 2 LITERATURE REVIEW | |
| 2.1 Energy generation | 5 |
| 2.1.1 Renewable energy | 7 |
| 2.1.1(a) Solar | 7 |
| 2.1.1(b) Wind | 7 |
| 2.1.1(c) Hydro | 7 |
| 2.1.1(d) Biomass | 7 |
| 2.1.2 Non-renewable energy | 9 |
| 2.1.2(a) Coal | 10 |
| 2.1.2(b) Crude Oil | 11 |
| 2.1.2(c) Natural gas | 11 |
| 2.2 Microbial Fuel Cell | 12 |

| | | |
|------------------------------|---|----|
| 2.2.1 | Microbial Fuel Cell History | 12 |
| 2.2.2 | Microbial Fuel Cell versus Conventional Fuel cell | 12 |
| 2.2.3 | Microbial Fuel Cell concept | 12 |
| 2.2.3(a) | Biological | 12 |
| 2.2.3(b) | Chemical | 13 |
| 2.2.3(c) | Electrical | 14 |
| 2.2.4 | Microbial Fuel Cell design | 15 |
| 2.2.4(a) | Single chamber | 16 |
| 2.2.4(b) | Double chamber | 16 |
| 2.2.4(c) | Stack | 17 |
| 2.2.4(d) | Flat plate | 17 |
| 2.2.4(e) | Tubular | 18 |
| 2.2.5 | Microbial Fuel Cell substrates | 19 |
| 2.3 | Food waste | 20 |
| 2.4 | Effect of parameter in MFC | 20 |
| 2.4.1 | moisture | 20 |
| 2.4.2 | Electrode distance | 21 |
| 2.4.3 | Temperature | 21 |
| 2.4.4 | pH | 21 |
| 2.5 | Polarization curve method in MFC | 22 |
| CHAPTER 3 METHODOLOGY | | |
| 3.1 | Equipments and Chemicals | 23 |
| 3.2 | Research methodology flow chart | 24 |
| 3.3 | Sample Collection | 25 |
| 3.4 | MFC configuration | 25 |
| 3.5 | Preparation of inoculum | 26 |
| 3.6 | Experimental Design | 26 |

| | | |
|--|--|----|
| 3.6.1 | Optimization of electricity generation using one-factor-at-one-time (OFAT) | 26 |
| 3.6.1(a) | Effect of pH | 26 |
| 3.7 | Analytical method | 27 |
| 3.7.1 | Determination of micronutrients and trace elements | 27 |
| 3.7.2 | Determination of macronutrients | 27 |
| 3.7.3 | Determination of substrate degradation efficiency (SDE) | 28 |
| 3.7.4 | Determination of electricity generation | 29 |
| 3.7.5 | Determination of biomass | 29 |
| 3.7.6 | Specific growth rate electrogenic bacteria | 30 |
| 3.7.7 | Doubling time to each electrogenic bacteria | 30 |
| CHAPTER 4 RESULTS AND DISCUSSIONS | | |
| 4.1 | Proximate analysis of food waste | 32 |
| 4.2 | Preliminary study on growth kinetic of different strain of EB in batch culture. | 34 |
| 4.3 | Effect of pH in ML-MFC | 36 |
| 4.3.1 | Effect of pH on EB Voltage generation and substrate degradation efficiency (SDE) in the ML-MFC | 36 |
| 4.3.2 | Effect of pH on EB growth in the ML-MFC | 39 |
| 4.3.3 | Effect of pH on Voltage generation and biomass growth in the ML-MFC. | 41 |
| 4.4 | ML-MFC performance | 42 |
| CHAPTER 5 CONCLUSION AND RECOMMENDATION | | |
| 5.1 | Conclusion | 45 |
| 5.2 | Recommendations | 45 |
| REFERENCES | | 46 |
| APPENDIX | | 50 |

LIST OF TABLES

| | Caption | Page |
|-----------|---|-------------|
| Table 2.1 | List of microbial fuel cell substrates | 19 |
| Table 3.1 | List of chemicals used and information | 23 |
| Table 3.2 | List of equipment used and information | 23 |
| Table 4.1 | Compounds analyse in food waste. | 32 |
| Table 4.2 | EB growth rate and doubling time | 35 |
| Table 4.3 | The comparison of the specific growth rate and doubling time for each EB. | 35 |
| Table 4.4 | Result of voltage generation and COD removal using one-factor-at-a-time (OFAT). | 38 |
| Table 4.5 | Power density at each pH | 42 |

LIST OF FIGURES

| | Caption | Page |
|-------------|---|-------------|
| Figure 2.1 | World energy generation in 2018 by IEA | 6 |
| Figure 2.2 | Pie chart electricity generation in Malaysia by Energy commission Malaysia 2017 | 10 |
| Figure 2.3 | Respiratory chain of anode and cathode reaction(Horan et al., 2018) | 14 |
| Figure 2.4 | MFC pathway | 15 |
| Figure 2.5 | Single chamber MFC | 16 |
| Figure 2.6 | Double chamber MFC | 16 |
| Figure 2.7 | Stacked MFC | 17 |
| Figure 2.8 | Flat plated MFC | 17 |
| Figure 2.9 | Tubular MFC | 18 |
| Figure 2.10 | Flowchart of food waste treatment by E-idaman sdn bhd. | 21 |
| Figure 3.1 | Flowchart of methodology | 24 |
| Figure 3.2 | ML-MFC design | 25 |
| Figure 4.1 | The trend of biomass vs Time of EB <i>geobacter</i> , <i>bacillus</i> , and mixed of <i>geobacter</i> and <i>bacillus</i> . | 34 |
| Figure 4.2 | Voltage generation of all varied pH | 37 |
| Figure 4.3 | Chemical oxygen demand versus time of varied pH | 38 |
| Figure 4.4 | Biomass ML-MFC of varied pH | 40 |
| Figure 4.5 | Biomass and Voltage profile of pH 8 | 41 |
| Figure 4.6 | Graph of power density over varied resistance of varied pH | 43 |
| Figure 4.7 | Polarization curve pH 8 | 44 |

LIST OF SYMBOLS

Caption

| | |
|-------------------------------|-----------------------------------|
| ° C | Celsius |
| kg/m ³ | kilogram per metre cube |
| mg | milligram |
| NaOH | Sodium hydroxide |
| NaClO ₂ | Sodium chlorite |
| c/kW.h | Cent per kilo Watt hour |
| mg / L | Milligram per litre |
| mW / m ² | milliwatt per meter cube |
| g | gram |
| M | Molar |
| HNO ₃ | Nitric acid |
| NAD ⁺ | nicotinamide adenine dinucleotide |
| FADH ₂ | Flavin adenine dinucleotide |
| CO ₂ | Carbon dioxide |
| H ₂ O ₂ | Hydrogen peroxide |
| V | Volt |
| I | Current |
| R | Resistance |
| P | Power |

LIST OF ABBREVIATIONS

| Abbreviation | Definition |
|---------------------|-------------------------------------|
| MFC | Microbial fuel cell |
| ML-MFC | Membrane less - microbial fuel cell |
| COD | Chemical oxygen demand |
| SDE | Substrate degradation efficiency |
| OFAT | One-factor-at-a-time |
| RE | Renewable energy |
| NRE | Non renewable energy |
| cm | Centimetre |
| MW | Microgram |
| mm | Millimetre |
| Abs | Absorbance |
| EJ | Exojoule |
| mV | milivolte |
| ATP | adenosine triphosphate |
| ppm | Parts per million |
| hr | Hour |
| mL | millilitres |

Abstrak

Bahan bakar fosil telah menyokong perindustrian dan pertumbuhan ekonomi negara-negara selama berabad-abad yang lalu dan jelas bahawa tidak dapat bertahan dalam jangka waktu yang lebih lama. Dalam kajian ini, Microbial Fuel cell (MFC) berpotensi untuk menghasilkan tenaga elektrik dan pada masa yang sama dapat mengurangkan banyak sisa makanan (1,64 kg / hari, sekitar 8 tan / tahun) yang dibuang di tempat sampah. MFC yang dikendalikan secara elektrokimia menggabungkan bakteria elektrogenik (EB) yang bertindak sebagai biopemangkin untuk menghasilkan elektrik. Prestasi MFC menggunakan sisa makanan dinilai menggunakan kaedah satu-faktor-pada-satu-saat (OFAT). Kajian ini fokus pada pengoptimuman pH untuk menghasilkan penjanaan tenaga yang lebih baik. Untuk menentukan elektrik yang dihasilkan, keluk polarisasi digunakan untuk menilai prestasi MFC. Permintaan oksigen kimia (COD) sisa makanan juga dipelajari. Pengoptimuman keadaan pH di MFC di bawah pH antara 5 hingga 9. Hasil kajian menunjukkan bahawa pH 8 adalah pH yang paling sesuai untuk strain *Bacillus* yang dipilih untuk eksperimen ini. Dengan voltan yang dihasilkan 807 mV, biojisim tertinggi 35.46 mg / L, dan ketumpatan kuasa menghasilkan 373.3 mW / m². Kesimpulannya, keadaan persekitaran pH di MFC akan mempengaruhi kecekapan pengeluaran tenaga. Peningkatan dalam EB juga meningkatkan voltan dalam ML-MFC, membuktikan bahawa jumlah EB dan voltan EB dikaitkan dengan pertumbuhan EB.

Abstract

Fossil fuels have supported the industrialization and economic growth of countries during the past centuries and it is clear that they cannot indefinitely sustain in a longer time. In this study, Microbial Fuel cell (MFC) had potential solution to generate electricity power and at the same time could reduce the abundant of food waste (1.64 kg/daily, around 8 tonnes/year) which dumped in the landfill. The MFC operated electrochemically incorporate electrogenic bacteria (EB) acted as a biocatalyst in order to produce electricity. The performance of the MFC using food waste is evaluated using one-factor-at-a-time (OFAT) method. the optimization performance of the MFC using food waste was evaluated using method of one factor at one time (OFAT) and it was focused to pH for power generation. To determine the generated electricity the polarization curve was used to evaluate the performance of MFC. The chemical oxygen demand (COD) of food waste is studied. Optimization of pH condition in MFC under certain pH ranging from 5 to 9, with other condition. Results shows that pH 8 is the most suitable pH for *Bacillus* strain that was chosen for this experiment. With voltage generated resulted 807 mV, highest biomass produced 35.46 mg/L, and power density produced 373.3 mW/m². In conclusion, pH environment condition in MFC will affect the efficiency of performance for energy production. The increase in EB biomass also increased the voltage in the ML-MFC, proving that EB biomass and voltage were associated with growth.