

COST COMPARISON OF SEISMIC DESIGN FOR
REINFORCED CONCRETE BUILDING UNDER
RANAU EARTHQUAKE

NOR AMELIA BINTI ADHA

SCHOOL OF CIVIL ENGINEERING
UNIVERSITI SAINS MALAYSIA
2017

**COST COMPARISON OF SEISMIC DESIGN FOR REINFORCED
CONCRETE BUILDING UNDER RANAU EARTHQUAKE**

By

NOR AMELIA BINTI ADHA

This dissertation is submitted to

UNIVERSITI SAINS MALAYSIA

As partial fulfilment of requirement for the degree of

**BACHELOR OF ENGINEERING (HONS.)
(CIVIL ENGINEERING)**

School of Civil Engineering,
Universiti Sains Malaysia

June 2017



**SCHOOL OF CIVIL ENGINEERING
ACADEMIC SESSION 2016/2017**

**FINAL YEAR PROJECT EAA492/6
DISSERTATION ENDORSEMENT FORM**

Title: COST COMPARISON OF SEISMIC DESIGN FOR REINFORCED
CONCRETE BUILDING UNDER RANAU EARTHQUAKE

Name of Student: NOR AMELIA BINTI ADHA

I hereby declare that all corrections and comments made by the supervisor(s) and
examiner have been taken into consideration and rectified accordingly.

Signature:

Approved by:

(Signature of Supervisor)

Date :

Name of Supervisor :

Date :

Approved by:

(Signature of Examiner)

Name of Examiner :

Date :

ACKNOWLEDGEMENT

First and foremost, my utmost gratitude express to my supervisor, Professor Dr. Taksiah A. Majid for giving me a lot of knowledge, encouragement and cooperation. With her generous guidance and advice I can finish up this project.

Thank you to Mrs. Tahara for guidance and sharing her knowledge with me during this research. I also would like to thank to my colleagues for lend me the structure books that useful in this thesis.

Lastly, thank you to my family for their support and pray for my successful to complete this thesis and also lend their ear during the hard time.

ABSTRAK

Sempadan plat aktif boleh menyebabkan gempa bumi pada lokasi yang berhampirannya termasuk Malaysia. Pada 5 Jun 2015, gempa bumi telah berlaku di Ranau, Sabah dengan magnitud 6.0 skala Richter. Kerosakan serius pada bangunan tertentu telah berlaku akibat daripada kesan gempa bumi ini. Oleh itu, jurutera struktur memerlukan penyelesaian untuk mengatasi masalah ini daripada berlaku lagi. Anggaran kos bagi bangunan reka bentuk seismik adalah penting bagi jurutera untuk menganalisis dan mendapat pemahaman yang lebih baik tentangnya. Justeru itu, anggaran kos kepada sektor pembinaan kos sebagai persediaan awal untuk pelancaran *Malaysia Annex* untuk Piawai Malaysia dalam masa terdekat. Kajian ini memberi tumpuan kepada perbandingan kos antara reka bentuk seismik dan bukan seismik untuk tiga, enam dan sembilan tingkat dengan bangunan seragam dan tidak seragam. Analisis telah dijalankan dengan menggunakan perisian SAP 2000 dan direka bentuk berdasarkan Eurocode 2 untuk rasuk dan tiang. Keputusan menunjukkan bahawa bangunan reka bentuk seismik mempunyai kos yang paling tinggi dalam tan tetulang dan isipadu konkrit berbanding reka bentuk bukan seismik. Jumlah kos bangunan tiga tingkat yang mengalami beban seismik untuk bangunan seragam adalah 7.9 % lebih tinggi berbanding dengan reka bentuk bangunan bukan seismik. Jumlah kos bangunan tiga tingkat yang mengalami beban seismik untuk bangunan tidak seragam adalah 21.9% lebih tinggi berbanding dengan reka bentuk bangunan bukan seismik. Seterusnya, jumlah kos bangunan enam tingkat di yang mengalami beban seismik untuk bangunan seragam adalah 43.2 % lebih tinggi berbanding dengan reka bentuk bangunan bukan seismik. Jumlah kos bangunan enam tingkat di yang mengalami beban seismik untuk bangunan tidak seragam adalah 46.9 % lebih tinggi berbanding dengan reka bentuk bangunan bukan seismik. Selain itu, jumlah kos bangunan sembilan tingkat

yang mengalami beban seismik untuk bangunan seragam adalah 13.1 % lebih tinggi berbanding dengan reka bentuk bangunan bukan seismik. Jumlah kos bangunan sembilan tingkat yang mengalami beban seismik untuk bangunan tidak seragam adalah 43.2 % lebih tinggi berbanding dengan reka bentuk bangunan bukan seismik.

ABSTRACT

Active plate boundaries can cause an earthquake to its nearest location including Malaysia. On 5th June 2015, an earthquake has occurred at Ranau, Sabah with magnitude of 6.0 Richter scale. Serious damages on certain building had occurred by the impact of this earthquake. Thus, structural engineers need solution to overcome this problem from happening again. The cost estimate for superstructure under seismic loading is important for engineers to analyze and have a better understanding on costing. Therefore, the cost estimation is important for Malaysia as preliminary information for construction player in preparation of the launch of Malaysia Annex to Standard Malaysia. This study focuses on comparison of cost between seismic and non-seismic design for three, six and nine storey with regular and irregular buildings. The analyses were carried out by using SAP 2000 software and calculated the beam and column design based on Eurocode 2. Results show that seismic design building has the higher cost in steel tonnage and concrete volume compared to the non-seismic design. The total cost of three storey under seismic design for regular building is 7.9 % higher compared to the non-seismic design building. The total cost of three storey under seismic design for irregular building is 21.9 % higher compared to the non-seismic design building. Next, the total cost of six storey under seismic design for regular building is 43.2 % higher compared to the non-seismic design building. The total cost of six storey under seismic design for irregular building is 46.9 % higher compared to the non-seismic design building. Besides that, the total cost of nine storey under seismic design for regular building is 13.1 % higher compared to the non-seismic design building. The total cost of nine storey under seismic design for irregular building is 43.2 % higher compared to the non-seismic design building.

TABLE OF CONTENTS

ACKNOWLEDGEMENT.....	ii
ABSTRAK	iii
ABSTRACT.....	v
TABLE OF CONTENTS	vi
LIST OF FIGURES	ix
LIST OF TABLES.....	xii
LIST OF ABBREVIATIONS	xvi
CHAPTER 1.....	1
1.1 Background.....	1
1.2 Problem Statement.....	3
1.3 Objectives.....	3
1.4 Scope of Work.....	4
CHAPTER 2.....	5
2.1 Past Earthquake Events.....	5
2.2 Previous Research in Costing.....	8
2.3 Summary.....	11
CHAPTER 3.....	13
3.1 Introduction.....	13
3.2 Seismic Mass Calculation.....	16

3.3	Calculation of Base Shear Due to Seismic Load.....	20
3.4	Lateral Load Distribution.....	21
3.5	Design Seismic Action of Design Spectrum.....	22
3.6	Behaviour Factor of Horizontal Seismic Actions.....	23
3.7	Analysis the Model.....	24
3.8	Beam and Column Design.....	27
CHAPTER 4.....		30
4.1	Introduction.....	30
4.2	The Fundamental Period of Vibration, T_1	30
4.3	The Base Shear Force, F_b	31
4.4	Beam Design.....	34
4.5	Column Design.....	37
4.6	Effect of Type of Loading on Total Amount Steel of Beam.....	40
	Reinforcement	
4.6.1	Model of Three Storey.....	40
4.6.2	Model of Six Storey.....	41
4.6.3	Model of Nine Storey.....	43
4.7	Effect of Type of Loading on Total Amount Steel of Column.....	44
	Reinforcement	
4.7.1	Model of Three Storey.....	44
4.7.2	Model of Six Storey.....	46
4.7.3	Model of Nine Storey.....	47
4.8	Effect of Type of Loading on Total Amount Concrete of Beam.....	48
	Reinforcement	
4.8.1	Model of Three Storey.....	48
4.8.2	Model of Six Storey.....	49

4.8.3	Model of Nine Storey.....	50
4.9	Effect of Type of Loading on Total Amount Concrete of Column....	51
	Reinforcement	
4.9.1	Model of Three Storey.....	51
4.9.2	Model of Six Storey.....	52
4.9.3	Model of Nine Storey.....	53
4.10	Effect of Type of Loading on Total Cost of Steel and Concrete.....	54
4.10.1	Model of Three Storey.....	55
4.10.2	Model of Six Storey.....	56
4.10.3	Model of Nine Storey.....	57
CHAPTER 5.....		60
5.1	Conclusion.....	60
5.2	Recommendation for Further Research.....	61
REFERENCES.....		62

APPENDIX

APPENDIX A: Mass Calculation, Base Shear and Horizontal Seismic

APPENDIX B: Calculation of Beam Design

APPENDIX C: Calculation of Column Design

APPENDIX D: Calculation Amount of Steel Tonnage and Concrete Volume

LIST OF FIGURES

Figure 1.1: Ranau earthquake on 5 th June, 2015.....	2
Figure 1.2: The crack at the bottom of column at Hospital Ranau.....	2
Figure 2.1: Building collapsed as result of Northridge earthquake.....	6
Figure 2.2: The remains of destroyed building.....	6
Figure 2.3: Crack on the pillar of the wall.....	7
Figure 2.4: Cost of structural systems in different seismic zones.....	9
Figure 3.1: The three story of building with regular frame.....	13
Figure 3.2: The three story of building with irregular frame.....	14
Figure 3.3: The six story of building with regular frame.....	14
Figure 3.4: The six story of building with irregular frame.....	15
Figure 3.5: The nine story of building with regular frame.....	15
Figure 3.6: The nine story of building with irregular frame.....	16
Figure 3.7: The step of beam and column analysis by using SAP 2000 software.....	26
Figure 3.8: The steps of beam design according to Eurocode 2 and 8.....	27
Figure 3.9: The steps of column design based on Eurocode 2 and 8.....	28
Figure 3.10: Flow chart of research methodology.....	29
Figure 4.1: The arrangement of interior support and exterior support.....	35

Figure 4.2: Comparison of earthquake and gravity loading affecting	40
the amount of beam reinforcement for three storey	
Figure 4.3: Comparison of earthquake and gravity loading affecting	42
the amount of beam reinforcement for six storey	
Figure 4.4: Comparison of earthquake and gravity loading affecting	43
the amount of beam reinforcement for nine storey	
Figure 4.5: Comparison of earthquake and gravity loading affecting	44
the amount of column reinforcement for three storey	
Figure 4.6: Comparison of earthquake and gravity loading affecting	46
the amount of column reinforcement for six storey	
Figure 4.7: Comparison of earthquake and gravity loading affecting	47
the amount of column reinforcement for nine storey	
Figure 4.8: Comparison of earthquake and gravity loading affecting	48
total volume concrete of beam reinforcement for three storey	
Figure 4.9: Comparison of earthquake and gravity loading affecting	49
total volume concrete of beam reinforcement for six storey	
Figure 4.10: Comparison of earthquake and gravity loading affecting	50
total volume concrete of beam reinforcement for nine storey	
Figure 4.11: Comparison of earthquake and gravity loading affecting	52
total volume concrete of column reinforcement for three storey	

Figure 4.12: Comparison of earthquake and gravity loading affecting	53
total volume concrete of column reinforcement for six storey	
Figure 4.13: Comparison of earthquake and gravity loading affecting	54
total volume concrete of column reinforcement for nine storey	
Figure 4.14: Comparison of earthquake and gravity loading affecting	55
total cost of steel reinforcement and volume concrete for three storey	
Figure 4.15: Comparison of earthquake and gravity loading affecting	56
total cost of steel reinforcement and volume concrete for six storey	
Figure 4.16: Comparison of earthquake and gravity loading affecting	58
total cost of steel reinforcement and volume concrete for six storey	

LIST OF TABLES

Table 2.1: Design PGA on rock site in Peninsular Malaysia, Sarawak and Sabah....	8
Table 2.2: The seismic zone consideration.....	10
Table 2.3: Summarize of previous research in costing.....	12
Table 3.1: The mass of three storey with regular shape of model.....	17
Table 3.2: The mass of six storey with regular shape of model	17
Table 3.3: The mass of nine storey with regular shape of model	18
Table 3.4: The mass of three storey with irregular shape of model.....	18
Table 3.5: The mass of six storey with irregular shape of model	19
Table 3.6: The mass of nine storey with irregular shape of model	19
Table 4.1: The fundamental period of vibration for three, six and nine storey	30
for regular model	
Table 4.2: The fundamental period of vibration for three, six and nine storey.....	31
for irregular model	
Table 4.3: The base shear force for three storey in regular shape.....	31
Table 4.4: The base shear force for six storey in regular shape.....	32
Table 4.5: The base shear force for nine storey in regular shape.....	32
Table 4.6: The base shear force for three storey in irregular shape.....	33
Table 4.7: The base shear force for six storey in irregular shape.....	33

Table 4.8: The base shear force for nine storey in irregular shape.....	34
Table 4.9: The main reinforcement, bending moment and shear.....	35
reinforcement in beam for three, six and nine storey	
for regular shape with seismic or non-seismic	
Table 4.10: The main reinforcement, bending moment and shear.....	36
reinforcement in beam for three, six and nine storey	
for irregular shape with seismic or non-seismic	
Table 4.11: The main reinforcement, axial force and shear.....	38
reinforcement in column for three, six and nine storey	
for regular shape with seismic or non-seismic	
Table 4.12: The main reinforcement, axial force and shear.....	39
reinforcement in column for three, six and nine storey	
for irregular shape with seismic or non-seismic	
Table 4.13: Comparison of earthquake and gravity loading on total.....	41
amount steel of beam reinforcement for three storey	
Table 4.14: Comparison of earthquake and gravity loading on total.....	42
amount steel of beam reinforcement for six storey	
Table 4.15: Comparison of earthquake and gravity loading on total	43
amount steel of beam reinforcement for nine storey	
Table 4.16: Comparison of earthquake and gravity loading on total.....	45
amount steel of column reinforcement for three storey	

Table 4.17: Comparison of earthquake and gravity loading on total.....	46
amount steel of column reinforcement for six storey	
Table 4.18: Comparison of earthquake and gravity loading on total.....	47
amount steel of column reinforcement for nine storey	
Table 4.19: Comparison of earthquake and gravity loading on total.....	49
volume concrete of beam reinforcement for three storey	
Table 4.20: Comparison of earthquake and gravity loading on total.....	50
volume concrete of beam reinforcement for six storey	
Table 4.21: Comparison of earthquake and gravity loading on total.....	51
volume concrete of beam reinforcement for nine storey	
Table 4.22: Comparison of earthquake and gravity loading on total.....	52
volume concrete of column reinforcement for three storey	
Table 4.23: Comparison of earthquake and gravity loading on total.....	53
volume concrete of column reinforcement for six storey	
Table 4.24: Comparison of earthquake and gravity loading on total.....	54
volume concrete of column reinforcement for nine storey	
Table 4.25: Comparison of earthquake and gravity loading on total.....	55
cost of steel reinforcement and concrete volume for three storey	
Table 4.26: Comparison of earthquake and gravity loading on total.....	57
cost of steel reinforcement and concrete volume for six storey	

Table 4.27: Comparison of earthquake and gravity loading on total.....58
cost of steel reinforcement and concrete volume for nine storey

LIST OF ABBREVIATIONS

f_{ck}	Concrete Compression Strength
f_{yk}	Strength of Steel
G_k	Dead Load
Q_k	Live Load
q	Behaviour Factor
F_b	Base Shear Force
m	Masses
F_i	Lateral Forces
T_1	Fundamental Period of Vibration

CHAPTER 1

INTRODUCTION

1.1 Background

Location of Malaysia is close to two seismically active plate boundaries which is the inter-plate boundary between the Indo-Australian and Eurasian Plate on west and the inter-plate boundary between the Eurasian and Philippines sea plates on east. Major earthquake events occur from this plate boundaries is still felt even though Malaysia is considered safe from earthquake. Peninsular and East Malaysia has experienced local earthquake such as at Bukit Tinggi (Pahang), Miri (Sarawak) and Ranau (Sabah). On 5th June 2015, earthquake measuring magnitude of 6.0 richter scale struck Ranau, Sabah and caused serious damages on structures. Due to Ranau earthquake, structural engineer are alarmed with the possible earthquake threat in Malaysia especially in Ranau, Sabah.

The cost estimation is important for Malaysia as preliminary information for construction player in preparing for the launch of Malaysia Annex (Lam et al 2016). The loading characteristics such as gravity and lateral loads also influence the structural cost as most buildings were designed without considering lateral load especially seismic. Thus, the structural cost of the superstructure would influence based on the difference type of loading which is seismic loading and non-seismic loading. Figure 1.1 and Figure 1.2 show the damages building occurred at Ranau, Sabah.




Figure 1.1 : Ranau earthquake on 5th June, 2015
 (U. S. Geological Survey, 2015)



Figure 1.2 : The crack at the bottom of column at Hospital Ranau

1.2 Problem Statement

In Malaysia, many buildings are constructed without considering seismic loading due to lack of awareness on recent earthquake threat. Nowadays, earthquake and its effects are concerned by the government and public on the seismic costing and its resistant especially on existing and newly buildings. Therefore, comprehensive earthquake resistance cost of building are needed for the cost management studies as to focus on the issue of cost implications on seismic resistance in buildings. Thus, cost comparison is important to ensure a better understanding on seismic resistance as preparation for the establishment of the Malaysia Annex in Eurocode 8. Therefore, this study is to carried out the costing by considering gravity and lateral (earthquake) loads to the structures.

1.3 Objectives

The objective of this project are :

1. The main objective for this study is to compare the structural cost of superstructure with and without earthquake loading in term of steel tonnage and concrete volume of the of reinforced concrete buildings.

1.4 Scope of work

The following are the scope of work for this study:

- i. Frames designed with gravity and earthquake loading according to Eurocode 8 and 2.
- ii. Model is designed by using SAP 2000 software according to the Eurocode 2 and Eurocode 8.
- iii. Soil type (B) which is very dense sand according to the Eurocode 8.
- iv. Costing of superstructure based on Standard Method of Measurement (SMM).
- v. The original model followed Hatzigeorgiou and Liolios (2010) in term of building configuration and design prospect.

CHAPTER 2

LITERATURE REVIEW

2.1 Past Earthquake Events

An earthquake magnitude of 6.7 occurred in Bingol, Turkey and caused 5617 buildings collapsed, 3509 had moderate damages and 3618 had light damages were reported. About 878 casualties were reported from this earthquake. This incident happened due to usage of poor material quality and quantity, poor in curing of concrete and designing the building without considering earthquake loading in building. The estimation of direct economic loss in the building stocks is approximately 250 million US dollars according to Dogangun (2004).

The earthquake struck in Lorca, Spain with magnitude of 4.5 causes structure become weak under first tremor. Nine people were death and 324 were injured. The failure of building is due to unawareness of actual seismic hazard, lenient prescription of design codes and lack of fulfilment of regulations and poor construction practices. The estimated losses of insured building in Spain earthquake cost about 332.5 millions of Euros (Valcarcel et al., 2012).

On 17th January 1994, Northridge earthquake magnitude of 6.4 hit the Los Angeles metropolitan area. This earthquake produced highest peak ground acceleration which is 1.8 g. From this earthquake, the estimate of damage is more than \$20 billion and 57 people were deaths. Figure 2.1 shows building collapsed as result of the Northridge earthquake.